



Mobilube PTX FE 75W-80

Mobil Passenger Vehicle Lube , Czech Republic

Automotive Gear Oil

Product Description

Mobilube PTX FE 75W-80 is a multipurpose gear lubricant. Mobilube PTX FE 75W-80 has been developed for latest generation of Porsche DCT gearboxes and transfer cases, to provide excellent fuel economy compared to 75W-90 grades, without compromising on transmission durability and functionality. It provides low temperature fluidity with high temperature stability ensuring excellent wear protection in these transaxles over a wide range of operating conditions.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Features and Benefits

The combination of synthetic base fluid technology and special high performance additives have been designed to provide excellent low temperature fluidity and fuel efficiency at same time, without compromising on wear protection as well as synchromesh compatibility and 'shiftability'.

- Excellent low temperature fluidity enables easier gear shifts at low temperature extremes compared to SAE 80W-90 and 75W-90 grades.
- Good synchromesh compatibility helps maintaining gear box functionality and durability
- High stability versus thermal and/or oxidative degradation
- High level of wear protection under some of the most severe conditions.
- Excellent fuel efficiency compared to conventional SAE 80W-90 and 75W-90 grades

Specifications and Approvals

This product has the following approvals:

ZF TE-ML 11

This product is recommended for use in applications requiring:

API GL-4

Properties and Specifications

Property	
Grade	SAE 75W-80
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	51.7
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.5
Pour Point, °C, ASTM D97	-57
Flash Point, Cleveland Open Cup, °C, ASTM D92	211
Density @ 15.6 C, g/ml, ASTM D4052	0.8525

Property	
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	20700

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2022

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved