



## MOBIL DCTF MULTI-VEHICLE

Mobil Passenger Vehicle Lube , Germany

Dual Clutch (Automatic) Transmission Fluid

### Product Description

Mobil DCTF Multi-Vehicle is a premium, fully synthetic lubricant formulated from selected high-quality synthetic base oils combined with an advanced additive system designed to meet the service fill needs of the broadest range of wet dual clutch transmissions in vehicles from European, North American and Asian car builders.

Its versatility of use is a plus for workshops aiming to ensure an optimal service to their customers while simplifying their operations and product management.

### Features and Benefits

Mobil DCTF Multi-Vehicle provides consistent all-weather smooth shifting and lubrication protection of the transmission components to help extend transmission service life and provide a comfortable driving experience.

Advantages offered by Mobil DCTF Multi-Vehicle:

- Applicable in wet DCT
- Exceptional oxidation stability and resistance to chemical deterioration — maintains long-lasting fluid quality and helps prolong transmission life
- Excellent lubricating characteristics for clutch friction durability, smooth shifting, and excellent wear protection
- Excellent viscosity stability to help assure adequate lubrication and to maintain excellent viscosity properties at low start-up temperatures and high operating temperatures
- Dependable protection against rust and corrosion
- Excellent seal performance to protect against fluid leakage and prevent component failures from oil starvation

### Applications

ExxonMobil supports Mobil DCTF Multi-Vehicle for service fill use in a broad range of vehicles equipped with wet dual clutch transmissions. This includes transmission types from Audi, BMW, Bugatti, Chrysler, Ford, Mitsubishi, Nissan, Peugeot, Citroen, Renault, Seat, Skoda, Volvo, Volkswagen...

Mobil DCTF Multi-Vehicle is not recommended for use in step type AT or CVT transmissions.

Based on internal testing, ExxonMobil supports the use of the product in the following applications:

OEM Vehicle marque	Quality Level The product is recommended by ExxonMobil for use in applications requiring:
BMW	DCTF-1 fluid BMW Drivelogic 7-speed (Getrag) transmission
BMW DCTF-1+	
BMW 6-speed DCT transmission	
BMW MTF LT-5	

OEM Vehicle marque	Quality Level The product is recommended by ExxonMobil for use in applications requiring:
Bugatti	Bugatti Veyron vehicle
CHRYSLER	GA fluid Chrysler 68044345 EA
Chrysler Powershift 6-speed (Getrag) transmission	
Ferrari	Ferrari 7-speed (Getrag)/TE DCT-3
FORD	Ford WSS-M2C936A fluid (part # 1490763/1490761) Ford Powershift 6-speed (GFT) transmission
MITSUBISHI	MZ320065 DiaQueen SSTF-1 fluid Mitsubishi TC-SST 6-speed (GFT) transmission
NISSAN	Nissan Powershift 6-speed (GFT)
PEUGEOT/CITROEN	9734.S2 fluid Peugeot/Citroen DCS 6-speed (GFT) transmission
RENAULT	Renault EDC 6-speed (Getrag) transmission
Renault EDC-7 transmission	
VOLVO	Volvo Powershift 6-speed (GFT) fluid (part# 1161838/1161839)
VW (Audi, Seat, Skoda)	VW (Audi, Seat, Skoda) 6-speed transmission
S-Tronic 7 G 052 529 A2 or A6 fluid DQ501 transmission	
G 052 182 A2 or A6 fluid DQ250 & DQ500 transmissions	
ZF/Porsche	ZF/Porsche Oil #999.917.080.00

## Notes:

- It is important to note that the respective vehicle manufacturers have not evaluated nor approved the product in these applications
- Mobil DCTF Multi-Vehicle should not be used in CVT, ATF type automatic transmissions.
- Good maintenance practice dictates that automatic transmissions be checked for proper fluid levels at regular intervals, and that the fluid be drained and replaced at intervals recommended by the manufacturer. Some manufacturers recommend more frequent changes of transmission fluid under severe driving conditions such as those that occur in heavy traffic, in hot weather, or when pulling a trailer.

## Properties and Specifications

Property	
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	12600
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	7.0

Property	
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	34.7
Pour Point, °C, ASTM D97	-66
Flash Point, Cleveland Open Cup, °C, ASTM D92	204

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen

Belgium

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.com/de-de/kontakt>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved