



Mobil Delvac 1320, 1330, 1340, 1350

Mobil Commercial Vehicle Lube , Denmark

Heavy Duty Diesel Engine Oils

Product Description

Mobil Delvac 1320, 1330, 1340, and 1350 are high performance, heavy duty diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off highway conditions. Mobil Delvac 1300 monogrades are used in a wide range of applications where a monograde lubricant is recommended.

Features and Benefits

| Features   | Advantages and Potential Benefits       |
|--|---|
| Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion | Prolonged engine life                   |
|  | Less wear                               |
|  | Excellent protection against ring stick |
| Extended TBN reserve   | Long-term deposit/wear control          |

Applications

- Naturally aspirated and turbo-charged diesel powered equipment
- On highway light and heavy duty trucking
- Off highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

| Mobil Delvac 1320 1330 1340 1350 are also recommended by ExxonMobil for use in applications requiring: | MOBIL DELVAC 1320 | MOBIL DELVAC 1330 | MOBIL DELVAC 1340 | MOBIL DELVAC 1350 |
|--|-------------------|-------------------|-------------------|-------------------|
| API CF   | X                 | X                 | X                 | X                 |
| API SF   | X                 | X                 | X                 | X                 |

Properties and Specifications

| Property                                      | MOBIL DELVAC 1320 | MOBIL DELVAC 1330 | MOBIL DELVAC 1340 | MOBIL DELVAC 1350 |
|---|-------------------|-------------------|-------------------|-------------------|
| Grade   | SAE 20            | SAE 30            | SAE 40            | SAE 50            |
| Ash, Sulfated, mass%, ASTM D874               | 1.3               | 1.3               | 1.3               | 1.3               |
| Density @ 15 C, g/ml, ASTM D4052              | 0.887             | 0.89              | 0.897             | 0.902             |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 232               | 256               | 240               | 260               |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 8.4               | 11.8              | 14.6              | 19.9              |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445  | 61                | 106               | 146               | 232               |

| Property                               | MOBIL DELVAC 1320 | MOBIL DELVAC 1330 | MOBIL DELVAC 1340 | MOBIL DELVAC 1350 |
|--|-------------------|-------------------|-------------------|-------------------|
| Pour Point, °C, ASTM D97               | -21               | -21               | -21               | -18               |
| Total Base Number, mgKOH/g, ASTM D2896 | 10.1              | 10.1              | 10.1              | 10.1              |
| Viscosity Index, ASTM D2270            | 108               | 99                | 99                | 99                |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024  
ExxonMobil Nordic  
Affiliate of ExxonMobil Nordic AS, Norway  
Gydevang 39-41  
DK-3450 Allerød, Denmark  
Tel: +45 45 99 02 10  
Fax : +45 45 99 02 80  
[www.exxonmobil.no](http://www.exxonmobil.no)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved