



Mobil 1™ FS X1 5W-50

Mobil Passenger Vehicle Lube , Denmark

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ is the world's leading synthetic motor oil brand delivering our ultimate performance and protection. The Mobil 1 technology keeps your engine running like new. Mobil 1™ FS x1 5W-50 is an advanced performance synthetic engine oil designed to help provide exceptional cleaning power.

Features and Benefits

Mobil 1™ FS x1 5W-50 is made with a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced component system providing:

- Engine wear protection and lubrication over the full oil drain interval.
- Excellent protection for your engine by helping to prevent the buildup of harmful deposits
- Enhanced cleaning technology for cars with higher mileage; 100 000km +
- Improved protection against variable fuel quality*
- Protection for your engine during start-up at low temperatures

* Performance compared in industry standard tests, which use fuels designed to promote sludge formation.

Applications

Mobil 1 FS x1 5W-50 is recommended for many types of vehicles with higher mileage; > 100 000 km

Specifications and Approvals

This product has the following approvals:
Porsche A40

This product is recommended for use in applications requiring:
API CF
FIAT 9.55535-M2

This product meets or exceeds the requirements of:
API SM
API SN
ACEA A3/B3

This product meets or exceeds the requirements of:

ACEA A3/B4

LEXUS LFA Service Fill

Properties and Specifications

Property	
Grade	SAE 5W-50
Noack Volatility, 1 h, 250 C, mass%, ASTM D5800	75
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	16.7
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	23000
Flash Point, Cleveland Open Cup, °C, ASTM D92	240
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	4.5
Base Number, mgKOH/g, ASTM D2896	13
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	6000
Shear Stability, Kinematic Viscosity @ 100 C, after Shear, mm ² /s, ASTM D6278	16.6
Pour Point, °C, ASTM D97	-45

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2022

ExxonMobil Nordic

Affiliate of ExxonMobil Nordic AS, Norway

Gydevang 39-41

DK-3450 Alleroed, Denmark

Tel: +45 45 99 02 10

Fax : +45 45 99 02 80

www.exxonmobil.no

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved