



Mobil Delvac Super Multigrades

Mobil Commercial Vehicle Lube , Ecuador

Heavy Duty Engine Oils

Product Description

Mobil Delvac Super 10W-30, 15W-40 and 20W-50 are high performance, heavy duty engine oils that provide proven protection to diesel engines operating in sev and off-highway service applications. Mobil Delvac Super Multigrade engine oils are recommended for use in a wide range of heavy duty applications and ope environments found in the trucking, construction, and agricultural industries. They are also suitable for gasoline engines.

Features and Benefits

The key benefits of Mobil Delvac Super Multigrades include:

| Features | Advantages and Potential Benefits |
|----------------------------------|--|
| Thermal and oxidation stability | Controls sludge build-up and deposits |
| Excellent detergency/dispersancy | Cleaner engines and longer engine life |
| Stay-in-grade shear stability | Helps reduce oil consumption and wear |

Applications

Recommended by ExxonMobil for use in:

- Diesel-powered equipment from leading diesel engine manufacturers
- On highway light and heavy duty trucking
- Off highway industries including: trucking, construction, quarrying, and agriculture
- Mixed diesel/gasoline engine fleets

Specifications and Approvals

| This product is recommended for use in applications requiring: | 10W-30 | 15W-40 | 20W-50 |
|--|--------|--------|--------|
| API CF-4 | X | X | X |
| API SF | X | X | X |
| API SG | | X | X |

Properties and Specifications

| Property | 10W-30 | 15W-40 | 20W-50 |
|------------------------------------|------------|------------|------------|
| Grade | SAE 10W-30 | SAE 15W-40 | SAE 20W-50 |
| Ash, Sulfated, mass%, ASTM D874 | 0.8 | 0.8 | 0.8 |
| Density @ 15.6 C, g/ml, ASTM D1298 | | | 0.88 |

| Property | 10W-30 | 15W-40 | 20W-50 |
|---|--------|--------|--------|
| Density @ 15.6 C, g/cm3, ASTM D4052 | 0.88 | 0.88 | |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 224 | 234 | 244 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 11.5 | 14.3 | 17.6 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 76 | 105 | 149 |
| Pour Point, °C, ASTM D97 | -33 | -27 | -30 |
| Total Base Number, mgKOH/g, ASTM D2896 | 8.2 | 8.2 | 8.2 |
| Viscosity Index, ASTM D2270 | 146 | 139 | 129 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

TERPEL-LUBRICANTES ECUADOR S.A.S.

Av. Joaquin Orrantia 125 y Av. de las Américas, Edificio Solaris, Piso 12, Oficinas 801-812, Guayaquil, Ecuador

Teléfono: (593) 4-3811980

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved