



Mobil Super™ Multigrado 10W-30

Mobil Passenger Vehicle Lube , Ecuador

Premium Quality Multigrade Semi Synthetic

Product Description

Mobil Super™ Multigrado 10W-30 is a premium semi-synthetic motor oil that meets the industry's latest engine oil specifications. The product is designed to provide a high level of performance and protection under most operating conditions.

Features and Benefits

Engine protection during start-up

Long-term protection against engine wear and deposit formation

Helps fight sludge

Mobil Super Multigrado 10W-30 is meticulously designed to meet today's most stringent engine specifications. It provides very good engine protection and promotes long engine life.

Applications

Mobil Super Multigrado 10W-30 has been formulated for use in almost all vehicles. ExxonMobil recommends the oil especially for everyday driving under normal conditions.

- Almost all gasoline engine technologies
- Passenger vehicles, SUVs, light trucks and vans
- Normal operating conditions
- Suitable for use in a wide range of temperature conditions

Always refer to your owner's manual to check the recommended viscosity grade and specifications for your specific vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:
GM 6094M

This product meets or exceeds the requirements of:
API SP
ILSAC GF-6A

This product meets or exceeds the requirements of:

API SP Resource Conserving

API SN PLUS

API SN PLUS RESOURCE CONSERVING

API SN Resource Conserving

API SN

API SM

API SL

API SJ

Chrysler MS-6395

Properties and Specifications

Property	
Grade	SAE 10W-30
Viscosity Index, ASTM D2270	149
Density @ 15.6 C, g/ml, ASTM D4052	0.8581
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	64
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 ⁽⁶⁾ sec ⁽⁻¹⁾ , mPa.s, ASTM D4683	3
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Pour Point, °C, ASTM D97	-39

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2023

TERPEL-LUBRICANTES ECUADOR S.A.S.

Av. Joaquin Orrantia 125 y Av. de las Américas, Edificio Solaris, Piso 12, Oficinas 801-812, Guayaquil, Ecuador

Teléfono: (593) 4-3811980

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

Exxon

Mobil

Esso

XTOMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved