



Mobil Super™ Semi Sintetico 5W-30

Mobil Passenger Vehicle Lube , Ecuador

Premium Semi-Synthetic Passenger Vehicle Engine Oil

Product Description

Mobil Super™ Semi Sintetico 5W-30 is an enhanced-premium semi-synthetic motor oil meeting the latest industry engine oil specifications. It is designed to provide an excellent level of protection and performance under the most demanding conditions.

Features and Benefits

Mobil Super Semi Sintetico 5W-30 is industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 5W-30 contains low friction semi-synthetic formulation which increases engine efficiency and offers greater fuel economy.

Mobil Super Semi Sintetico 5W-30 provides:

- Helps to promote long engine life
- Thanks to its semi-synthetic formulation provides improved fuel economy up to a 3%* by enabling the engine to work more efficiently
- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start up
- Excellent high temperature protection thanks to its high quality base oil formulation

*Potential fuel economy improvement obtained by switching from the most common higher viscosity oils to a lower viscosity grade, based on M111FE data by independent test lab. Actual savings are dependent upon vehicle/engine type, outside temperature, driving conditions and your current engine oil viscosity.

Applications

Mobil Super Semi Sintetico 5W-30 products is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Stop and Go City Driving
- Normal to severe operating conditions
- Turbo-Chargers

- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:
GM 6094M

This product meets or exceeds the requirements of:
API SP
ILSAC GF-6A
API SP Resource Conserving
API SN PLUS
API SN PLUS RESOURCE CONSERVING
API SN Resource Conserving
API SN
API SM
API SL
API SJ
Ford WSS-M2C946-A
Ford WSS-M2C946-B1
FORD WSS-M2C961-A1

Properties and Specifications

Property	
Grade	SAE 5W-30
Viscosity Index, ASTM D2270	152
Density @ 15.6 C, g/ml, ASTM D4052	0.8581
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	63
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 ⁽⁶⁾ sec ⁽⁻¹⁾ , mPa.s, ASTM D4683	3

Property	
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	6040
Flash Point, Cleveland Open Cup, °C, ASTM D92	220
Pour Point, °C, ASTM D97	-39

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

Terpel-Comercial Ecuador Compañía Limitada

Dirección : Av. Joaquín Orrantía, Edificio Solaris, Piso 12, Oficinas (801-812), Guayaquil – Ecuador

Teléfono: +593 42634060

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved