



Mobil Super™ Semi Sintetico 5W-30

Mobil Passenger Vehicle Lube , Ecuador

Premium Quality Synthetic Technology Oil for Passenger Vehicle Engines

Product Description

Mobil Super™ Semi Sintetico 5W-30 is an enhanced, premium-quality, synthetic technology engine oil that meets the latest engine oil specifications in the industry. It is designed to provide an excellent level of protection and performance under the most demanding conditions.

Features and Benefits

Mobil Super™ Semi Sintetico 5W-30 has been fully tested in the industry so you can have confidence that you'll get the performance you want from your vehicle. The product contains a low-friction synthetic technology formulation that increases engine efficiency and provides improved fuel economy.

Mobil Super™ Semi Sintetico 5W-30 provides:

- Helps promote long engine life
- Thanks to its synthetic technology formulation, it provides improved fuel economy by up to 3%* by allowing the engine to run more efficiently
- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start-up.
- Excellent protection at high temperatures thanks to its formulation with a high-quality base oil.

*Potential fuel economy improvement from the most common higher viscosity oils to a lower viscosity grade, based on M111FE data provided by an independent testing laboratory. Actual savings depend on the type of vehicle/engine, outside temperature, road conditions, and the viscosity of your current motor oil.

Applications

Mobil Super™ Semi Sintetico 5W-30 is formulated to give you confidence that your engine is receiving protection that goes far beyond what conventional oils can provide. We recommend it in particular for the following vehicle types and conditions:

- The latest gasoline engine technologies

- Passenger vehicles, SUVs, light trucks and vans
- Driving in the city with many stops
- Normal to severe operating conditions
- Turbochargers
- High-performance engines

Always refer to your owner's manual to check the recommended viscosity grade and specifications for your specific vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:

GM 6094M

This product meets or exceeds the requirements of:

API SP

ILSAC GF-6A

API SP Resource Conserving

API SN PLUS

API SN PLUS RESOURCE CONSERVING

API SN Resource Conserving

API SN

API SM

API SL

API SJ

Ford WSS-M2C946-A

Ford WSS-M2C946-B1

FORD WSS-M2C961-A1

Properties and Specifications

Property	
Grade	SAE 5W-30
Viscosity Index, ASTM D2270	152
Density @ 15.6 C, g/ml, ASTM D4052	0.8581
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	63
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	6040
Flash Point, Cleveland Open Cup, °C, ASTM D92	220
Pour Point, °C, ASTM D97	-39

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2024

TERPEL-LUBRICANTES ECUADOR S.A.S.

Av. Joaquin Orrantia 125 y Av. de las Américas, Edificio Solaris, Piso 12, Oficinas 801-812, Guayaquil, Ecuador

Teléfono: (593) 4-3811980

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved