



Mobil 1™ FS 5W-30

Mobil Passenger Vehicle Lube , Estonia

Advanced Fully Synthetic Engine Oil

Product Description

Mobil 1™ is the world's leading synthetic motor oil brand delivering our ultimate performance and protection. The Mobil 1 technology keeps your engine running like new. Mobil 1™ FS 5W-30 is an advanced performance synthetic engine oil designed to help provide exceptional cleaning power and provides improved protection against variable fuel quality (1).

Features and Benefits

Mobil 1™ FS 5W-30 is made with a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced component system providing :

- Engine wear protection and lubrication over the full oil drain interval.
- Excellent protection for your engine by helping to prevent the buildup of harmful deposits.
- Improved protection against variable fuel quality (1)
- Potential fuel economy improvement when switching from higher viscosity oils (2)
- Provides outstanding high temperature protection over the entire oil drain interval

(1) Performance compared in industry standard tests, which use fuels designed to promote sludge formation.

(2) Actual savings are dependent upon vehicle/engine type, ambient weather, driving conditions and your current engine oil viscosity.

Applications

Mobil 1™ FS 5W-30 is recommended for many types of European vehicles.

To be used for high performance engines in Volkswagen, Audi, Skoda, Mercedes Benz, Renault and other cars requiring the specifications and approvals listed below

Specifications and Approvals

This product has the following approvals:
BMW Longlife 01
MB-Approval 229.5
MB-Approval 229.3
RENAULT RN0700
RENAULT RN0710
VW 502 00

This product has the following approvals:

VW 505 00

AVTOVAZ (LADA cars)

This product is recommended for use in applications requiring:

API CF

This product meets or exceeds the requirements of:

API SL

ACEA A3/B4

API SP ENGINE TEST REQUIREMENTS

AAE (STO 003) Group B7

Properties and Specifications

Property	
Grade	SAE 5W-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	237
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	71.8
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12.2
Density @ 15.6 C, g/ml, ASTM D4052	0,840
Viscosity Index, ASTM D2270	168
Pour Point, °C, ASTM D97	-39

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved