



## Mobil Super™ 3000 Formula M 5W-30

Mobil Passenger Vehicle Lube , Estonia

Mobil passenger-vehicle-lube , United Kingdom High performance engine oil

### Product Description

Mobil Super™ 3000 Formula M 5W-30 is a high performance full SAPS engine oil primarily intended for use in Mercedes Benz , BMW and VW vehicles where a product for extended service intervals (Long Life) is required.

### Features and Benefits

Mobil Super 3000 Formula M 5W-30 offers excellent performance at both very low and very high operating temperatures and long term engine protection from wear and sludge.

### Applications

Mobil Super 3000 Formula M 5W-30 is recommended for long drain servicing of gasoline and diesel engine passenger cars or light commercial vehicles calling for any of the specifications listed below. It is a full SAPS (high ash) formulation providing the extra protection needed for engines without ATS (exhaust gas after-treatment systems) or operating in regions with fuels with higher sulfur content.

### Specifications and Approvals

#### This product has the following approvals:

MB-Approval 229.3

MB-Approval 229.5

VW 502 00

VW 505 00

BMW Longlife 01

AVTOVAZ (Lada cars) Group "Premium"

#### This product meets or exceeds the requirements of:

API SL

API SP ENGINE TEST REQUIREMENTS

ACEA A3/B3

ACEA A3/B4

AAE (STO 003) Group B7

## Properties and Specifications

Property	
Grade	SAE 5W-30
Pour Point, °C, ASTM D97	-42
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	12.1
Viscosity Index, ASTM D2270	159
Density @ 15.6 C, g/ml, ASTM D4052	0.847
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	74.8
Flash Point, Cleveland Open Cup, °C, ASTM D92	240

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>


All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2022

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003–2023 Exxon Mobil Corporation. All Rights Reserved