



## Mobil Delvac™ 1310

Mobil Commercial Vehicle Lube , Egypt

High Performance Hydraulic Oil

### Product Description

Mobil Delvac™ 1310 is a high performance hydraulic oil formulated from advanced base oils and a balanced additive system designed to satisfy a wide range of heavy-duty hydraulic equipment requirements. It is formulated using an effective balance of dispersants and detergents combined with inhibitors to control oxidation, wear, corrosion and rust. Mobil Delvac 1310 is used in a wide range of on-road and off-road hydraulic applications.

### Features and Benefits

Mobil Delvac 1310 delivers excellent performance in a wide range of hydraulic systems and components. Mobil Delvac 1310 has excellent resistance to oxidation and its high levels of anti-wear protection help to extend equipment life. Mobil Delvac 1310 is compatible with other engine oils in case of accidental mixtures. The key features and benefits include:

Features	Advantages and Potential Benefits
Good protection against oil thickening, high temperature deposits, varnish and oil degradation	Clean hydraulic systems Less wear especially in vanes and control valves Protects against vane sticking Extends drain intervals with oil analysis
Good anti-wear protection	Reduces premature wear & extends equipment life
Wide temperature range performance	Reduces wear at cold start-up temperatures Effective lubrication film strength at high temperatures
Protects against rust and corrosion	Long equipment life and lower maintenance costs

### Applications

On-road and off-road applications industries including trucking, construction, mining, quarrying, and agriculture requiring Caterpillar TO-2 or Vickers 35VQ25 quality fluids

Hydraulic systems containing gears and bearings where good anti-wear properties are required

Hydraulic systems and components used in conjunction with equipment from leading American, European and Japanese manufacturers

### Properties and Specifications

Property	
Grade	SAE 10W
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	6.8
Viscosity Index, ASTM D2270	115

Property	
Total Base Number, mgKOH/g, ASTM D2896	7.5
Pour Point, °C, ASTM D97	-35

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2021 Exxon Mobil Corporation. All Rights Reserved