



Mobil Delvac Legend™ X3 50

Mobil Commercial Vehicle Lube , Egypt

Heavy Duty Diesel Engine Oil

Product Description

Mobil Delvac Legend X3 50 is a heavy duty diesel engine oil specifically engineered for performance in intercooled, turbo-charged engines operating under heavy conditions. Mobil Delvac Legend X3 50 is used in a wide range of applications where a monograde lubricant is recommended such as Trucking, quarrying, and agricultural businesses.

Features and Benefits

The features and benefits of Mobil Delvac Legend X3 50 include:

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Helps to prolong engine life, protect against ring sticking and to control wear

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment
- light, medium and heavy duty trucking
- Construction, quarrying and agriculture applications

Specifications and Approvals

This product is recommended for use in applications requiring:
API CF

Properties and Specifications

Property	
Grade	SAE 50
Total Base Number, mgKOH/g, ASTM D2896	7
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	213.8
Pour Point, °C, ASTM D97	-24
Flash Point, Cleveland Open Cup, °C, ASTM D92	276

Property	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	18.9
Viscosity Index, ASTM D2270	99

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2022

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>


+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved