



Mobil Coolant Advanced Ready Mixed 33%

Mobil Passenger Vehicle Lube , Egypt

High Performance Coolant

Product Description

Mobil™ Coolant Advanced Ready Mixed 33% is a high performance coolant designed to provide efficient protection down to -24°C during winter condition . It is a ready to use product that has been premixed with 33% Mobil antifreeze and 67% water.

Nitrite-, amine-, phosphate-, silicate-, borate-free coolant based on ethylene glycol

Features and Benefits

Mobil Coolant Advanced Ready Mixed 33% provides following benefits:

- Outstanding protection against frost and overheating in all modern engines, but especially highly loaded aluminum engines.
- Effective protection against corrosion and deposits in the cooling system vital parts.
- Easy circulation through the engine block and cylinder head channels, the radiator, and the heater enabling cooler operation and protection of the engine.

Applications

Mobil Coolant Advanced Ready Mixed 33% contains Glysantin® G30® from BASF approved by:

VW, Audi, Bentley, Bugatti, Lamborghini, Skoda, Seat TL 774-D/F, MAN 324-SNF, MTU MTL 5048, MINI Cooper D (vehicles built as from 2007), Porsche (vehicles built until 1996)

Mobil Coolant Advanced Ready Mixed 33% should not be mixed with other engine coolants. Most coolant blends are based on carefully balanced mixtures of various corrosion inhibitors. Mixing of coolants with different inhibitor packages can lead to loss of corrosion protection.

Properties and Specifications

Property	
Color, Visual	Red
Density @ 15.6 C, g/ml, ASTM D4052	1.05
Refractive Index, 20 C, ASTM D1218	1.37
MEG, vol %, CALCULATED	33
pH, ASTM D1287	7.8

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.asp>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved