



Mobil 1™ FS X1 5W-40

Mobil Passenger Vehicle Lube , Egypt

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ is the world's leading synthetic motor oil brand delivering our ultimate performance and protection. The Mobil 1 technology keeps your engine running like new. Mobil 1™ FS x1 5W-40 is an advanced performance synthetic engine oil designed to help provide exceptional cleaning power.

Features and Benefits

Mobil 1™ FS x1 5W-40 is made with a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced component system providing :

* Performance compared in industry standard tests, which use fuels designed to promote sludge formation.

- Engine wear protection and lubrication over the full oil drain interval.
- Excellent protection for your engine by helping to prevent the buildup of harmful deposits
- Enhanced cleaning technology for cars with higher mileage; 100 000km +
- Improved protection against variable fuel quality*
- Protection for your engine during start-up at low temperatures

Applications

Mobil 1 FS x1 5W-40 is recommended for many types of vehicles with higher mileage; > 100 000 km

- To be used for high performance engines in Volkswagen, Audi, Skoda, Porsche, Mercedes Benz and other cars requiring the specifications and approvals listed below

Specifications and Approvals

This product has the following approvals:

MB-Approval 229.3

Porsche A40

AVTOVAZ (LADA cars)

This product meets or exceeds the requirements of:

ACEA A3/B3

ACEA A3/B4

API SN

API SM

API SL

This product meets or exceeds the requirements of:

API SJ

AAE (STO 003) Group B7

Properties and Specifications

Property	
Grade	SAE 5W-40
Density @ 15 C, g/cm ³ , ASTM D4052	0.85
Flash Point, Cleveland Open Cup, °C, ASTM D92	228
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	82.5
Pour Point, °C, ASTM D97	-42

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt


You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved