



Mobilgrease MP

Mobil Passenger Vehicle Lube , Egypt

Lithium Automotive Grease

Product Description

Mobilgrease MP is a high quality, multipurpose, NLGI 2 grade, lithium hydroxystearate grease based on an ISO VG 150 mineral oil. It is formulated to provide added protection against rusting and water washout in general purpose automotive applications at moderate temperatures and loads.

Features and Benefits

Mobilgrease MP has a long history of proven performance in general purpose automotive applications and provides the following benefits:

- Wide operating temperature range
- Good resistance to water washout
- Extra protection against rust and corrosion
- Good pumpability in centralized systems
- Excellent structural stability
- Lead, chlorine and nitrite free

Applications

Mobilgrease MP is recommended for the lubrication of automotive chassis components, wheel bearings, clutch bearings, universal joints and ball joints of steering and suspension systems of passenger cars, trucks, farm tractors and most other types of mobile equipment operating under moderate conditions. The recommended operating temperature range of Mobilgrease MP is -20°C to 120°C. In applications where heavy or shock loading is a factor, extreme pressure greases are preferred.

Properties and Specifications

Property	
Grade	NLGI 2
Penetration, 60X, 0.1 mm, ASTM D217	280
Color, Visual	Medium Brown
Dropping Point, °C, ASTM D2265	180
Base Oil Viscosity of Greases @ 40 C, mm ² /s, AMS 1697	150

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved