



Mobil Super 1000 20W-50

Mobil Passenger Vehicle Lube , Egypt

Premium Multigrade Passenger Vehicle Engine Oils

Product Description

Mobil Super 1000 20W-50 is a premium quality mineral motor oils. The product is designed to provide protection for your engine under most operating conditions.

Features and Benefits

Mobil Super 1000 provides engine protection and helps promote long engine life.

- Extended protection against engine wear and deposits formation
- Engine protection during start up
- Helps combat sludge

Applications

Mobil Super 1000 20W-50 has been formulated to be suitable for use in vehicles requiring an API SL claim . ExxonMobil particularly recommend Mobil Super 1000 for daily driving under normal conditions:

- Passenger cars, SUV's, light trucks and vans (Gasoline engines) requiring an API SL
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil Super 1000 meets or exceeds the requirements of:	20W-50
API SL	X

Typical Properties

Mobil Super 1000	
SAE Grade	20W-50
St @ 40°C	174
cSt @ 100°C	19
Viscosity Index, ASTM D 2270	124
Sulfated Ash, wt%, ASTM D 874	0.8
HTHS Viscosity., mPa•s @ 150°C, ASTM D4683	4.7

Mobil Super 1000	
Pour Point, °C, ASTM D 97	-24
Flash Point, °C, ASTM D 92	240
Density @ 15 °C, kg/l, ASTM D4052	0.8928

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

02-2021

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved