



Chainsaw Oil

Mobil Industrial , Spain

Product Description

Chainsaw Oil is specifically developed for the lubrication of chain and guide bars of modern chain saws. Selected mineral base oils are combined with special additives to provide good protection against wear, rust and corrosion. Chainsaw Oil has good low temperature flow properties which makes it suitable for outside applications even during the winter season.

Features and Benefits

| Features | Advantages and Potential Benefits |
|---|---|
| Good adherence to metal surfaces | Stays well in place on saw chains and guide bars and ensures optimum component lifetime |
| Excellent protection against wear, rust and corrosion | Contribution toward increased chain and guide bar life and reduced maintenance costs as wear related failures are reduced |
| Low pour point | Ensures flow ability even at low operating temperatures for higher efficiency |

Applications

Chainsaw Oil can be used in hand-held or machine operated chain saws as specified by the manufacturer. It is suitable for lubrication of chains, slideways and guides in industrial applications, where a lubricant with good adherence, protection against wear, rust and corrosion and a low pour point is required.

Properties and Specifications

| Property | |
|--|-----|
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 220 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 11 |
| Pour Point, °C, ASTM D97 | -24 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2023

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical b.v.b.a.

Polderdijkweg

B-2030 Antwerpen, Belgium


<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit

www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved