



Mobil Super™ 3000 x1 Formula FE 5W-30

Mobil Passenger Vehicle Lube , Spain

Fully Synthetic Engine Oil

Product Description

Mobil Super™ 3000 engine oil series are synthetic and engineered to deliver outstanding protection.

Mobil Super™ 3000 x1 Formula FE 5W-30 provides long engine life with enhanced protection over a wide temperature range for many types and ages of vehicles including passenger cars, light commercial vehicles and vans.

Features and Benefits

Mobil Super™ 3000 x1 Formula FE 5W-30 provides:

- Enhanced high temperature protection
- Enhanced cold start-up performance
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection
- Helps fuel economy (as per ACEA A5/B5)
- Suitable for use in both gasoline and diesel engine passenger cars, light commercial vehicles and vans.

Applications

Mobil Super 3000 x1 Formula FE 5W-30 is recommended if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress.

- Mobil Super 3000 x1 Formula FE 5W-30 can be used in a variety of gasoline and diesel automobiles, light trucks and vans designed for use of a low viscosity (HTHS) motor oil.
- Mobil Super 3000 x1 Formula FE 5W-30 is intended primarily to meet the requirements of Ford in all engines requiring WSS-M2C913-D / C and is also suitable for use in Jaguar and Land Rover vehicles where the viscosity and quality claims are appropriate.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
STJLR.03.5003
VW VWC 53036

This product is recommended for use in applications requiring:
API CF

This product meets or exceeds the requirements of:

API SL

API SP

ACEA A5/B5

FORD WSS-M2C913-D

Properties and Specifications

Property	
Grade	SAE 5W-30
Density @ 15.6 C, g/ml, ASTM D4052	0.849
Flash Point, Cleveland Open Cup, °C, ASTM D92	229
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.7
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	52.9
Viscosity Index, ASTM D2270	170
Pour Point, °C, ASTM D97	-36

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical b.v.b.a.

Polderdijkweg

B-2030 Antwerpen, Belgium

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved