



Mobil 1™ ESP LV 0W-30

Mobil Passenger Vehicle Lube , Spain

Advanced Full Synthetic Engine Oil

Product Description

Mobil 1™ ESP LV 0W-30 is an advanced full synthetic engine oil specifically designed to provide outstanding performance.

Features and Benefits

Features	Advantages and Potential Benefits
Low viscosity, advanced full synthetic formulation	Promotes engine efficiency and fuel economy
Active cleaning agents	Helps prevent sludge and deposits to keep engines clean
Outstanding high temperature thermal and oxidative stability	Resists oil breakdown to help provide long lasting protection
Excellent low temperature capabilities	Outstanding cold starting and fast lubrication to protect against wear
Precise balance of performance additives	Excellent overall lubrication and wear protection

Applications

Mobil 1 ESP LV 0W-30 is a technology developed to meet the latest JLR STJLR.03.5007 specification for the JLR 2.0 L Ingenium 4 cylinder diesel engines.

Specifications and Approvals

This product has the following approvals:
BMW Longlife 12 FE
MB-Approval 229.61
VOLVO 95200377
STJLR.03.5007

This product is recommended for use in applications requiring:
FORD WSS-M2C920A

This product meets or exceeds the requirements of:
API SN Engine Test Requirements
API SL

This product meets or exceeds the requirements of:

ACEA A5/B5

ACEA C2

Properties and Specifications

Property	
Grade	SAE 0W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.7
Viscosity Index, ASTM D2270	180
Ash, Sulfated, mass%, ASTM D874	0.8
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	3.0
Pour Point, °C, ASTM D97	-51
Flash Point, °C, ASTM D93	200
Density @ 15.6 C, g/cm ³ , ASTM D4052	0.8429

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical b.v.b.a.

Polderdijkweg

B-2030 Antwerpen, Belgium

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved