



Mobilube™ S 80W-90

Mobil Commercial Vehicle Lube , Finland

Multi-Purpose Drivetrain Lubricant

Product Description

Mobilube™ S 80W-90 is an extra high performance drivetrain lubricant engineered to provide excellent lubrication for state-of-the-art, heavy duty manual transn components used in on-highway commercial vehicles and cars. Potential benefits include excellent shifting performance, good low temperature fluidity, an temperature viscosity retention. Mobilube S 80W-90 provides API GL-4/5 level performance.

Features and Benefits

Today's technology has vastly improved the performance capabilities of on-highway vehicles in terms of load, speed, and control through inno-drivetrain designs. designs have increased the requirements of components and lubricants to deliver a higher level of performance. For heavy-duty applications, friction control reduction, thermal stability, shear stability, rust and corrosion inhibition, and seal protection are features that must be optimally balanced to contribute to long ge synchroniser life, smooth shift control, fuel economy, and high load capability over a wide range of applications. Mobilube S 80W-90 delivers outstanding perform: current as well as older units. The key benefits include:

| Features | Advantages and Potential Benefits |
|---|---|
| Outstanding load carrying, anti-wear, and extreme pressure performance | Helps to promote long transmission life. |
| Excellent prevention of deposits and lacquer formation | Helps to promote long seal life, extended drain, and service intervals |
| Excellent protection from corrosion of copper and its alloys | Helps to promote long life of synchronisers and smoother shifting performance |
| Effective thermal and oxidation resistance at high operating temperatures | Helps to promote reduced wear and long component life |
| Excellent shear stability | Maintains effective viscosity and film strength during severe operation |
| Good low-temperature fluidity | Easier, smoother shifting and quicker starts |

Applications

- Recommended by ExxonMobil for use in:
- Cars, on highway light and heavy duty trucks, busses, and vans
 - Heavy duty automotive type drivetrains where API GL-4/GL-5 level performance is required

Specifications and Approvals

| This product has the following approvals: |
|---|
| Mack GO-J |
| MAN 341 Typ Z2 |
| MAN 342 Typ M2 |
| ZF TE-ML 02B |
| ZF TE-ML 05A |
| ZF TE-ML 12L |

| |
|--|
| This product has the following approvals: |
| ZF TE-ML 12M |
| ZF TE-ML 16B |
| ZF TE-ML 19B |
| ZF TE-ML 21A |

| |
|---|
| This product is recommended for use in applications requiring: |
| API GL-4 |
| MAN 341 Typ E2 |
| Meritor O76-D |
| MIL (US) MIL-PRF-2105E |
| ZF TE-ML 08 |

| |
|---|
| This product meets or exceeds the requirements of: |
| API GL-5 |
| API MT-1 |
| R. Bosch AS TE-ML 08 |
| ISUZU Axle Oil |
| Scania STO 1:0 |
| ISUZU Large Manual Transmission Oil |
| ZF TE-ML 07A |
| SCANIA STO 1:1G |

Properties and Specifications

| Property | |
|---|------------|
| Grade | SAE 80W-90 |
| Density @ 15 C, g/cm3, ASTM D4052 | 0.9 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 210 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 15 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 144 |
| Pour Point, °C, ASTM D97 | -30 |
| Viscosity Index, ASTM D2270 | 105 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2023

ExxonMobil Finland Oy Ab

Satamatie 10

21100 Naantali - FINLAND

+358 (0) 10 40 8500

<http://www.mobil.fi>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved