# **Mobil**<sup>®</sup>

## Mobil Super™ 3000 Formula P 5W-30

Mobil Passenger Vehicle Lube , Finland

High Performance Motor Oil

### Product Description

Mobil Super™ 3000 engine oil series are synthetic and engineered to deliver outstanding protection.

Mobil Super 3000 Formula P 5W-30 is a high performance, low ash engine oil designed to help prolong engine life and maintain the efficiency of the exhaust en reductionsSystems in both diesel and gasoline powered passenger cars, light commercial vehicles and vans.

This product is recommended for use in Peugeot, Citroen vehicles and a wide range of European cars and light-duty commercial vehicles which need to meet or  $\epsilon$  requirements of ACEA C2.

#### Features and Benefits

Mobil Super 3000 Formula P 5W-30 delivers excellent high and low temperature wear-protection and improved engine cleanliness.

Key features and benefits:

• Low Ash, low phosphorous and low sulfur formulation helping to prolong the life and maintain the efficiency of the emission reduction systems in both Dies Gasoline powered engines.

- Compatible with Diesel Particulate Filters and Catalytic Convertors.
- Help achieve fuel economy (as per ACEA C2).
- Excellent low temperature capabilities for reliable cold weather starting allowing fast engine and electrical system protection.
- High performance wear-protection.
- Active cleaning agents reducing deposits and sludge build-up to enable long and clean engine life.

#### Applications

Mobil Super 3000 Formula P 5W-30 is recommended for a variety of modern automotive engines, especially the high-performance gasoline, turbo-diesel injectic common rail and other diesel engines, found in the latest passenger cars, SUV's and light vans.

- · Peugeot-Citroen passenger cars and light commercial vehicles or vans
- · Passenger cars and light commercial vehicles or vans requiring ACEA C2 like lveco and Fiat vans
- Gasoline and Diesel with Diesel Particulate Filters (DPF) and Catalytic Convertors
- Normal to occasionally severe operating conditions (including city driving conditions)

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle. Not recommended for 2-cycle or a

engines, unless specifically approved by the manufacturer.

#### Specifications and Approvals

This product has the following builder approvals:
Peugeot/Citroën Automobiles B71 2290
This product meets or exceeds the requirements of:
ACEA C2

#### Properties and Specifications

Property	
Grade	SAE 5W-30
Density @ 15 C, g/ml, ASTM D4052	0.85
Flash Point, °C, ASTM D92	226
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.5
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	60
Phosphorus, mass%, ASTM D4951	0.08
Pour Point, °C, ASTM D97	-39
Ash, Sulfated, mass%, ASTM D874	0.7

#### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2021 ExxonMobil Finland Oy Ab Satamatie 10 21100 Naantali - FINLAND

#### +358 (0) 10 40 8500 http://www.mobil.fi

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All primary not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intenoverride or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

nose obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perform
al manufacture and at different blending locations. The information contained berein is subject to change without notice. All or



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved