



Mobilube HD 85W-140

Mobil Commercial Vehicle Lube , Fiji

Heavy Duty Automotive Gear Lubricants

Product Description

Mobilube HD 85W-140 is high performance, heavy duty gear lubricants formulated from high performance base oils and an advanced additive system. The lubricant is engineered for automotive applications including heavy duty axles and final drives where extreme pressures and shock loading are expected. It is recommended by ExxonMobil for applications where API GL-5 service is required.

Features and Benefits

Today's heavy equipment applications place higher performance demands on drive train lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximise equipment life and optimise operating costs. Longer service intervals place additional demands on the gear lubricant requiring effective basestock and additive systems. Mobilube HD 85W-140 is engineered to meet these challenges. The key benefits include:

| Features | Advantages and Potential Benefits |
|--|---|
| Exceptional thermal stability and resistance to high temperature oxidation | Extended gear and bearing life due to minimal deposits Longer seal life" |
| Outstanding protection against low speed/high torque wear and against high speed scoring | Increased load carrying capability Reduced maintenance costs and longer equipment life |
| Excellent rust and corrosion protection | Reduced wear and longer component life |
| Effective low temperature lubrication | Improved startability |
| Compatible with typical automotive seals and gaskets | Minimum leakage and reduced contamination |

Applications

Recommended by ExxonMobil for use in:

- Heavy duty axles and final drives requiring API GL-5 level performance.
- Passenger cars, on highway light and heavy duty trucks and commercial vehicles.
- Off highway industries including: construction, mining, quarrying, and agriculture.
- Other heavy duty industrial and automotive applications involving hypoid gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque prevail.

Specifications and Approvals

| |
|---|
| This product meets or exceeds the requirements of: |
| API GL-5 |

Properties and Specifications

| Property | |
|--|-------------|
| Grade | SAE 85W-140 |
| Brookfield Viscosity @ -12 C, mPa.s, ASTM D2983 | 100000 |
| Density @ 15 C, g/ml, ASTM D4052 | 0.9 |
| Flash Point, °C, ASTM D92 | 236 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 27.5 |
| Pour Point, °C, ASTM D97 | -24 |
| Viscosity Index, ASTM D2270 | 97 |
| Shear Stability (KRL 20h), mm ² /s, CEC L-45-A-99 | 27 |


Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2022

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved