

# Mobil Super™ 1000 10W-30

Mobil Passenger Vehicle Lube , Fiji

Everyday Protection Premium Mineral Engine Oil

#### **Product Description**

Mobil Super™ Everyday Protection is a premium mineral engine oil that delivers proven protection to extend engine life. Formulated with the ExtEngine™molecular age-defying, anti-wear ingredient, Mobil Super™ Everyday Protection reacts to engine-damaging stress by creating a long-lasting protective barrier for 65%^ wear protection. Mobil Super™ Everyday Protection meets or exceeds the requirements of the highest engine oil performance standards. Suitable for older Japand Korean cars including Toyota, Honda, Nissan, Daihatsu, Suzuki, Mitsubishi, Hyundai, and more.

#### Features and Benefits

- Premium mineral engine oil for everyday protection
- ExtEngine molecules for a long-lasting protective barrier to extend engine life
- 65% better engine wear protection^
- Meets or exceeds the latest industry standards

### **Applications**

ExxonMobil recommends Mobil Super™ Everyday Protection for daily driving under normal conditions:

- Older engine technologies
- Gasoline and diesel engines
- Passenger cars, SUVs, light trucks and vans

Always consult your owner's manual to check the recommended viscosity grade and specifications for your particular vehicle.

## Specifications and Approvals

This product has the following approvals:
APISP
API SN PLUS
APISN
APISM
APISL
ILSAC GF-6A
API CF

#### **Properties and Specifications**

<sup>^</sup> Based on Sequence IVB (Iron Wear) test result vs. API SP engine test.

Property	
Grade	SAE 10W-30
Viscosity Index, ASTM D2270	149
Total Base Number, mgKOH/g, ASTM D2896	7.5
Density @ 15.6 C, g/ml, ASTM D4052	0.858
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	64
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	8900
Ash, Sulfated, mass%, ASTM D874	0.8
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	226

# Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2022

