



**Airclean Oil**

Mobil Industrial , France  
Oil for vapour recovery equipment

**Product Description**

Airclean Oil is based on a high quality and narrow cut base oil for use in aluminium plant vapour recovery systems. It contains carefully selected oxidation inhibitors, make the oil extremely stable against oxidation at high temperatures and ensure a long service life.

**Features and Benefits**

Airclean Oil is manufactured to the strictest quality standards to provide to the user reliable and prolonged operation in service. The highly refined base oil, ca selected oxidation inhibitors are important performance features to ensure consistent characteristics of the fluid over time. Additionally the narrow distillation allows thorough recovery and recycling of roll oils without contamination with Airclean Oil. Some of the features and potential benefits offered by this oil are:

- Highly stable against oxidation
- Long service life
- Stable operation of distillation unit
- Narrow distillation cut
- Efficient recovery of roll oils
- Reduced consumption of roll oil

**Applications**

Airclean Oil is recommended for use as scrubber oil in vapour recovery systems in aluminium rolling plants. Airclean Oil is particularly designed to operate with Sor rolling oils which boiling characteristics allow easy distillation of roll oils without contamination with the scrubber oil.

**Properties and Specifications**

Property	
Appearance, AMS 1738	Clear and Bright
Density @ 15.6 C, kg/m3, ASTM D4052	863
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	31
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	5.4
Pour Point, °C, ASTM D97	-15
Flash Point, Cleveland Open Cup, °C, ASTM D92	>200

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2024

**Esso Société Anonyme Française**

20 rue Paul Héroult  
92000 Nanterre, France

Société Anonyme au capital de 98 337 521,70 euros

RCS Nanterre 542 010 053

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.fr/fr-fr/contact-us>

Tel. +33 (0)1 49 67 90 00

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved