



Mobil ATF™ D 21065

Mobil Passenger Vehicle Lube , France

Automatic Transmission Fluid

Product Description

Mobil ATF D 21065 is an Automatic Transmission Fluid blended to a unique formulation using highly refined base oils and performance additives. This transmission fluid is approved as a factory fill for PSA.

Features and Benefits

- Long transmission life.
- Outstanding friction durability for improved shift feel.
- Excellent cold flow properties.

Specifications and Approvals

According to ExxonMobil, this product is of the following quality level:

GM DEXRON IID

This product has the following approvals:

ZF TE-ML 04D

ZF TE-ML 11B

MB-Approval 235.71

PSA S71 2102

This product is recommended by ExxonMobil for use in applications requiring:

ZF TE-ML 09

Properties and Specifications

Property	
Density @ 15 C, kg/l, ASTM D4052	868
Flash Point, Cleveland Open Cup, °C, ASTM D92	208
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	7.4
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	38.2
Viscosity Index, ASTM D2270	164

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise

11-2022

Esso Société Anonyme Française

20 rue Paul Hérault
92000 Nanterre, France

Société Anonyme au capital de 98 337 521,70 euros

RCS Nanterre 542 010 053

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.fr/fr-fr/contact-us>

Tel. +33 (0)1 49 67 90 00

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved