



MOBIL DELVAC LEGEND™ 1300 SERIES

Mobil Commercial Vehicle Lube , Gabon

Monograde diesel engine oil

Product Description

Mobil Delvac Legend 1300 Series are excellent monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Mobil Delvac Legend 1300 Series are used in a wide range of applications where a monograde lubricant is recommended. Trucking, mining, quarrying, construction, and agricultural businesses use these products successfully.

Features and Benefits

The features and benefits of Mobil Delvac Legend 1300 series include:

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life, Less wear and Excellent protection against ring sticking
Extended TBN reserve	Long-term deposit/wear control and Controls formation of acids when using higher sulfur fuels

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment
- Light, Medium and heavy duty trucking
- Construction, mining, quarrying, and agriculture applications

Specifications and Approvals

This product is recommended for use in applications requiring:	MOBIL DELVAC LEGEND 1330	MOBIL DELVAC LEGEND 1340	MOBIL DELVAC LEGEND 1350
Allison C-4	X		
API CF	X	X	X
API SF	X	X	X

Properties and Specifications

Property	MOBIL DELVAC LEGEND 1330	MOBIL DELVAC LEGEND 1340	MOBIL DELVAC LEGEND 1350
Grade	SAE 30	SAE 40	SAE 50

Property	MOBIL DELVAC LEGEND 1330	MOBIL DELVAC LEGEND 1340	MOBIL DELVAC LEGEND 1350
Ash, Sulfated, mass%, ASTM D874	1.1	1.1	1.1
Density @ 15 C, g/cm3, ASTM D4052		0.81	
Flash Point, Cleveland Open Cup, °C, ASTM D92	235		250
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	11.6	11.6	19.5
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	101	101	222
Pour Point, °C, ASTM D97	-27	-27	-15
Total Base Number, mgKOH/g, ASTM D2896	10	10	10
Viscosity Index, ASTM D2270	99	99	99

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2024

MOBIL OIL GABON

Zone Industrielle d'Oloumi, PO Box 145

Libreville

+ 241 74 23 01

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved