



Mobilube XHP 75W-80

Mobil Commercial Vehicle Lube , United Kingdom

Manual Automotive Transmission Fluid

Product Description

Mobilube XHP 75W-80 is an extra high performance manual transmission lubricant engineered for the latest, European heavy duty manual transmissions used in on highway commercial vehicles and cars. This transmission lubricant is designed using select base oils and an advanced additive package that enhances shifting performance, low temperature fluidity, and high temperature viscosity retention. Mobilube XHP 75W-80 is formulated with extended performance reserve for applications requiring API GL-3/4 service.

Features and Benefits

Today's technology has vastly improved the performance capabilities of on highway vehicle load, speed, and control through innovative drivetrain designs. These designs have increased the requirements of lubricants to deliver a higher level of performance. For heavy duty manual transmissions, friction control, wear reduction, thermal stability, shear stability, rust and corrosion inhibition, and seal protection are features that must be optimally balanced to provide extended gear and synchroniser life, smooth shift control, fuel economy, and high load capability over a wide range of applications. Mobilube XHP 75W-80 delivers exceptional performance in current as well as older model manual transmissions. The key benefits include:

| Features | Advantages and Potential Benefits |
|---|---|
| Excellent load carrying, anti-wear, and extreme pressure performance | Extended transmission life and reduced operating costs |
| Excellent protection against deposit and lacquer formation | Longer seal life with extended drain and service intervals |
| Maximum protection from corrosion of copper and its alloys | Protects and extends the life of synchronisers while delivering smoother shifting performance |
| Effective thermal and oxidation protection at high operating temperatures | Reduces wear and maintenance costs |
| Excellent shear stability | Maintains effective viscosity and film strength during severe operation |
| Outstanding low-temperature fluidity | Easier, smoother shifting, and quicker starts |
| Extended service capability | Lower operating costs and higher productivity |

Applications

Recommended by ExxonMobil for use in:

- Heavy duty manual transmissions and gear cases where API GL-3/4 level performance is required
- Passenger cars, on highway light and heavy duty trucks, busses, and vans
- Where extended service and warranties are required

Specifications and Approvals

| Mobilube XHP 75W-80 is recommended by ExxonMobil for use in applications requiring: | |
|---|---|
| API GL-3/4 | X |
| MAN 341 Type E3 | X |

Typical Properties

| Mobilube XHP 75W-80 | |
|----------------------------------|--------|
| SAE Grade | 75W-80 |
| Viscosity, ASTM D 445 | |
| cSt @ 40°C | 52.2 |
| cSt @ 100°C | 9.5 |
| Viscosity Index, ASTM D 2270 | 168 |
| Pour Point, °C, ASTM D 97 | -45 |
| Flash Point, °C, ASTM D 92 | 226 |
| Density @ 15°C kg/l, ASTM D 4052 | 0.87 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobilube XHP are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.co.uk/en-gb/contact-us-technical>

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved