



MOBIL™ VACTRA SLIDEWAY SERIES

Mobil Industrial , United Kingdom

Way and Slide Lubricants

Product Description

Mobil™ Vactra Slideway are high-quality slideway lubricants specifically designed for the lubrication of linear motion guides, ball screws and slideways of high precision machine tools and metal processing machines. In particular, Mobil™ Vactra Slideway demonstrate exceptional friction performance and coolant separability. Mobil™ Vactra Slideway are carefully formulated from high-quality base stocks and the latest advanced additive system that provides controlled frictional properties for high precision machining, compatibility with aqueous metal working fluids and corrosion protection of parts and equipment. The unique additive package provides excellent frictional properties on a wide variety of way materials, including steel on steel and steel on polymer, reducing stick-slip and chatter. This allows smooth, uniform motion at design travel speeds enhancing machine productivity and very high accuracy helping to prolong tool life and enhance surface finish. Mobil™ Vactra Slideway have also been optimized to provide separability from many aqueous coolants.

Features and Benefits

Mobil™ Vactra Slideway have been specifically designed to provide excellent machinery protection and machining accuracy by satisfying the stringent demands of machine tool slideways. Mobil™ Vactra Slideway exhibit excellent lubricity and load-carrying performance contributing significantly to improving the quality of machined parts even at sub-micron level.

Mobil™ Vactra Slideway have been developed with adhesiveness which prevents lubricants from being washed away from slideways. Lubricant wash-away by coolant can be responsible for abnormal noises, increase in sliding resistance, overload of sliding motors stopping operations and decrease in machining accuracy. Mobil™ Vactra Slideway can help prevent these disturbances, even in applications with high-levels of coolant wash-away effect.

Mobil™ Vactra Slideway demonstrate outstanding separability from coolants which allows the machine tool to operate with high precision and help maximize the life and performance of coolants.

In addition, Mobil™ Vactra Slideway have been tested and optimized for compatibility with Mobil Vactra™ Oil Numbered Series.

| Features | Advantages and Potential Benefits |
|---|---|
| Controlled frictional characteristics | Reduces stick slip and improves machining accuracy for high-precision applications even at sub-micron level |
| Adhesiveness | Prevents washing lubricant out of critical surfaces |
| Water and Aqueous Coolant Separability | Helps improve the life and performance of many aqueous coolants |
| Long term rust and corrosion protection | Helps reduce the deterioration of sliding surfaces in the presence of water and aqueous coolants |
| Multi-material Capabilities | Suitable for a wide range of slideway material combinations allowing for product consolidation |

Applications

Mobil™ Vactra Slideway are recommended for the lubrication of machine tool slideway systems. They are designed for use with combinations of cast iron, steel and non-metallic way materials. Mobil™ Vactra Slideway may be applied by hand, forced-feed lubricator or in flood application by circulation system.

- Recommended for horizontal slideways on small to medium size machine tools in high precision applications. It is also suitable for circulating application in large machines and as a moderate duty hydraulic fluid.
- Can be used for lubrication of ball screws, linear guides, headstocks, translating screws.
- Recommended for applications where oil contamination of the aqueous coolants shortens coolant batch life.

Specifications and Approvals

| This product is recommended for use in applications requiring: | MOBIL VACTRA SLIDEWAY 68 | MOBIL VACTRA SLIDEWAY 220 |
|--|--------------------------|---------------------------|
| Fives Cincinnati P-47 | X | |
| Fives Cincinnati P-50 | | X |

| This product meets or exceeds the requirements of: | | |
|--|---|---|
| China GB 11118.1-2011, L-HG | X | X |
| DIN 51502:1990-08 CGLP | X | X |
| ISO L-GA (ISO 6743-13:2002) | X | X |
| ISO L-GB (ISO 6743-13:2002) | X | X |

Properties and Specifications

| Property | MOBIL VACTRA SLIDEWAY 68 | MOBIL VACTRA SLIDEWAY 220 |
|---|--------------------------|---------------------------|
| Grade | ISO VG 68 | ISO VG 220 |
| Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130 | 1B | 1B |
| FZG Scuffing, Fail Load Stage, A/8.3/90, ISO 14635-1 | 12 | 12 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 245 | 255 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 70,5 | 218.4 |
| Pour Point, °C, ASTM D97 | -12 | -12 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2024

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.co.uk/en-gb/contact-us-technical>

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is

intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved