



Mobil ATF™ D 21065

Mobil Passenger Vehicle Lube , United Kingdom

Automatic Transmission Fluid

Product Description

Mobil ATF D 21065 is an Automatic Transmission Fluid blended to a unique formulation using highly refined base oils and performance additives. This transmission fluid is approved as a factory fill for PSA.

Features and Benefits

- Long transmission life.
- Outstanding friction durability for improved shift feel.
- Excellent cold flow properties.

Specifications and Approvals

| |
|--|
| According to ExxonMobil, this product is of the following quality level: |
| GM DEXRON IID |

| |
|---|
| This product has the following approvals: |
| ZF TE-ML 04D |
| ZF TE-ML 11B |
| MB-Approval 235.71 |
| PSA S71 2102 |

| |
|--|
| This product is recommended by ExxonMobil for use in applications requiring: |
| ZF TE-ML 09 |

Properties and Specifications

| Property | |
|---|------|
| Density @ 15 C, kg/l, ASTM D4052 | 868 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 208 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 7.4 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 38.2 |
| Viscosity Index, ASTM D2270 | 164 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise

11-2022

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.co.uk/en-gb/contact-us-technical>

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved