



## Mobil Ultra 10W-40

Mobil Passenger Vehicle Lube , Georgia

Premium Quality Multigrade Passenger Vehicle Engine Oil

### Product Description

Mobil Ultra 10W40 is a premium quality motor oil for many types of gasoline and Diesel vehicles.

### Features and Benefits

Mobil Ultra 10W-40 is formulated with a proprietary mixture of premium and super premium quality base oils with an additive technology delivering very high performance and engine protection under a variety of driving conditions. Mobil Ultra 10W-40 reduces engine wear with excellent high and low temperature performance.

### Applications

Mobil Ultra 10W-40 can be used in a variety of passenger vehicles , light trucks and vans, and for anyone seeking a dependable super premium quality product.

### Specifications and Approvals

|                                                                                     |
|-------------------------------------------------------------------------------------|
| <b>This product is recommended by ExxonMobil for use in applications requiring:</b> |
| MB 229.1                                                                            |

|                                                                       |
|-----------------------------------------------------------------------|
| <b>This product is recommended for use in applications requiring:</b> |
| ACEA A3/B3-16                                                         |

|                                                                                                |
|------------------------------------------------------------------------------------------------|
| <b>This product meets or exceeds the requirements of the following industry specification:</b> |
| API SJ                                                                                         |
| API SL                                                                                         |
| API SM                                                                                         |
| API SN                                                                                         |
| API SN PLUS                                                                                    |

### Properties and Specifications

|                 |            |
|-----------------|------------|
| <b>Property</b> |            |
| Grade           | SAE 10W-40 |

| Property                                                              |      |
|-----------------------------------------------------------------------|------|
| Ash, Sulfated, mass%, ASTM D874                                       | 1    |
| Density @ 15.6 C, g/ml, ASTM D4052                                    | 0.87 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92                         | 230  |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 3.6  |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445            | 13.2 |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445             | 88.7 |
| Pour Point, °C, ASTM D97                                              | -42  |
| Viscosity Index, ASTM D2270                                           | 150  |

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2024

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved