



Mobil Delvac 1™ 5W-30 Advanced Synthetic

Mobil Commercial Vehicle Lube , Hong Kong

High Performance Advanced Synthetic Formula Low Ash Diesel Engine Oil

Product Description

Mobil Delvac 1™ 5W-30 Advanced Synthetic is an advanced synthetic heavy duty diesel engine oil for long and reliable service. The development of this product summarizes more than 90 years of ExxonMobil's research and development knowledge. The goal was to define a product that addresses all features required with modern on-highway truck applications, including those with emission control systems¹. This top performance product offers unsurpassed oxidation stability³ which results in engine cleanliness promoting efficient and smooth engine operation. The robustness of Mobil Delvac 1™ 5W-30 Advanced Synthetic meets or exceeds the longest oil drain intervals defined by major global manufacturers, offering protection during extended oil drains up to 100,000 miles¹. It was also developed and tested to protect the engine with the use of biofuel components to consider different diesel fuel qualities and future, sustainability related fuel components. The advanced lubricant formulation helps to gain fuel economy benefits in modern engine applications². The outstanding wear protection performance of Mobil Delvac 1™ 5W-30 Advanced Synthetic is the result of extensive and close cooperative development work of ExxonMobil with major equipment builders. As a result, this product meets or exceeds the requirements of the latest API and ACEA industry specifications for diesel engine oils, as well as the requirements of many major American, and European engine manufacturers.

¹ Please refer to the owner's handbook for OEM application requirements and oil drain intervals for your vehicle or equipment.

² Compared to an SAE 15W-40 engine oil. Actual savings are dependent on vehicle engine type, outside temperature, driving conditions, and your current engine oil viscosity.

³ Based on PC-11 industry test data.

Features and Benefits

Mobil Delvac 1™ 5W-30 Advanced Synthetic is an outstanding lubricant solution for modern and latest engine technology equipped with emission After-Treatment devices. It was developed by ExxonMobil to maintain unsurpassed oxidation stability performance to meet long oil drain intervals and support low maintenance efforts. Mobil Delvac 1™ 5W-30 Advanced Synthetic keeps at the same time critical and hot engine parts clean, also while bio diesel fuel components are used, for long and efficient engine life. This feature, in combination with the sophisticated additive system, ensures exceptional engine wear performance and supports long engine life. The low ash formulation protects at the same time all exhaust after-treatment parts required to meet emissions regulations.

Features	Advantages and Potential Benefits
Unsurpassed thermal and oxidation stability	Prevention of deposits and smooth engine operation
Step out wear protection	Reduced engine wear to promote long engine life
Bio fuel compatible	Maintains engine cleanliness and protection with bio fuel components
Enhanced fuel economy potential	Reduced fuel consumption
Extended drain interval capability	Fewer oil changes and less oil disposal
Emission system protection	Emissions system durability and performance

Specifications and Approvals

This product has the following approvals:

This product has the following approvals:

Detroit Detroit Fluids Specification 93K222

DQC IV-18 LA

MACK EOS-4.5

MAN M 3677

MAN M 3775

MB-Approval 228.51

MB-Approval 228.52

MTU Oil Category 3.1

RENAULT VI RLD-3

VOLVO VDS-4.5

This product meets or exceeds the requirements of:

API CJ-4

API CK-4

API SN

JASO DH-2

ACEA E6

ACEA E7

ACEA E9

Caterpillar ECF-3

Cummins CES 20086

DAF Extended Drain

Properties and Specifications

Property	
Grade	SAE 5W-30
Viscosity Index, ASTM D2270	160
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	73
Pour Point, °C, ASTM D97	-42

Property	
Density @ 15 C, g/ml, ASTM D1298	0.851
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12
Flash Point, Cleveland Open Cup, °C, ASTM D92	241

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2021

ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong

+852 3197 8888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003–2019 Exxon Mobil Corporation. All Rights Reserved