



## Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty

Mobil Commercial Vehicle Lube , Honduras

Mobil commercial-vehicle-lube

### Product Description

Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty is a high performance diesel engine oil that provides proven engine protection of diesel engines operating in on and off-highway severe service applications. Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

### Features and Benefits

The technology in Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty delivers excellent performance in both modern diesel engines as well as older models. Provides up to an average of 30% more viscosity control<sup>1</sup>.

Features	Advantages and Potential Benefits
Provides up to an average of 40% more valve train wear protection <sup>1</sup>	Longer engine life
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Clean engines and long engine life
Thermal and oxidation stability	Controls sludge build-up and deposits

1. Compared to API CH-4 standard. Based on Sequence IIIF and RFWT engine test.

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from Chinese, European, Japanese, and American manufacturers.
- On-highway light and heavy-duty trucking.
- Off-highway industries including: construction, mining, quarrying, and agriculture.

### Specifications and Approvals

<b>This product has the following approvals:</b>
MB-Approval 228.3
MTU Oil Category 2

<b>This product meets or exceeds the requirements of:</b>
---

**This product meets or exceeds the requirements of:**

API CH-4

API SJ

Cummins CES 20076

**Properties and Specifications**

Property	
Grade	SAE 15W-40
Viscosity Index, ASTM D2270	137
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	115.9
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	15.21
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Density @ 15 C, kg/l, ASTM D4052	0.87

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2021

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved