



Mobil Super™ 3000 Formula V 0W-20

Mobil Passenger Vehicle Lube , Croatia

Synthetic Engine Oil

Product Description

Mobil Super™ 3000 engine oil series are synthetic, and engineered to deliver outstanding protection.

Mobil Super™ 3000 Formula V 0W-20 is a high performance grade engine oil formulated to provide long engine life for modern gasoline and diesel vehicles equipped with After Treatment Systems (e.g. DPF) and requiring a low viscosity oil to achieve enhanced fuel economy.

Features and Benefits

Mobil Super 3000 Formula V 0W-20 is designed to help :

- improve fuel economy in both diesel and gasoline powered engines
- enhance engine cleanliness and sludge prevention
- enhance high temperature and wear protection
- enhance cold start-up performance

Applications

Mobil Super 3000 Formula V 0W-20 is recommended for new emerging diesel and gasoline powered European vehicles where a SAE 0W-20 viscosity grade is required. It meets or exceeds the requirements of Volkswagen for the standards stated below. These specifications are not backward compatible with the earlier VW specifications.

Specifications and Approvals

This product has the following approvals:

VW 508 00

VW 509 00

Porsche C20

This product meets or exceeds the requirements of:

ACEA C5

API SN PLUS

Properties and Specifications

| Property | |
|----------|-----------|
| Grade | SAE 0W-20 |

| Property | |
|--|-------|
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 8.1 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 41.4 |
| Pour Point, °C, ASTM D97 | -45 |
| Phosphorus, mass%, ASTM D4951 | 0.08 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 236 |
| Density @ 15 C, g/ml, ASTM D1298 | 0.842 |
| Ash, Sulfated, mass%, ASTM D874 | 0.8 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2022

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved