



MOBILUBE PTX 75W-90

Mobil Passenger Vehicle Lube , Croatia

Axle Oil

Product Description

Mobilube PTX is a SAE 75W-90 multipurpose gear lubricant. It has been developed to provide outstanding performance specifically in Porsche 911 transaxles. It provides low temperature fluidity with high temperature stability ensuring excellent wear protection in these transaxles over a wide range of operating conditions.

Features and Benefits

The combination of synthetic base fluid technology and special high performance additives have been carefully formulated to meet the low temperature requirements of Porsche. It also provides excellent synchromesh compatibility and 'shiftability', whilst maintaining excellent wear protection.

Mobil PTX provides the following benefits:

- Excellent low temperature fluidity, giving easier gear changing from cold over conventional SAE 80W-90 and 75W-90 grades.
- Excellent synchromesh compatibility / durability.
- Good thermal /oxidative stability.
- High level of wear protection under some of the most severe conditions.

Specifications and Approvals

| | |
|--|---|
| MOBILUBE PTX 75W-90 has the following approval: | |
| Approved TE-ML 11 | X |

| | |
|--|---|
| According to ExxonMobil, Mobilube PTX 75W-90 is of the following quality level: | |
| API GL-4 | X |
| API GL-5 | X |

Typical Properties

| | |
|----------------------------|------|
| MOBILUBE PTX 75W-90 | |
| Viscosity | |
| cSt @ 100°C | 14.5 |
| cSt @ 40° C | 77.6 |
| Viscosity Index | 195 |
| Flash Point, °C | 226 |
| Pour Point, °C | -60 |
| Density kg/m ³ | 849 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommended

provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This p should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype and the Pegasus design are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

05-2020

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon Mobil Esso XTO
CORPORATION

© Copyright 2003-2024 Exxon Mobil Corporation. All
Rights Reserved