



## HYDRAULIC OIL AW SERIES

Mobil Industrial , Haiti

Hydraulic Oil

### Product Description

Hydraulic AW Oil Series oils are good quality anti-wear hydraulic oils intended for industrial and mobile service applications, subjected to moderate operating conditions and requiring anti-wear lubricants.

Their effective oxidation resistance and chemical stability support good oil life in moderate applications.

### Features and Benefits

- Good anti-wear performance helps reduce pump wear and prolonging pump life
- Corrosion protection helps reduce the effects of moisture on system components
- Filterability to prevent filter blockage even in the presence of water

### Applications

- Systems using gear, vane, radial and axial piston pumps and those containing gears and bearings where mild anti-wear characteristics are required
- Where hydraulic oil contamination or leakage is unavoidable
- Where small amounts of water are unavoidable

### Specifications and Approvals

| This product meets or exceeds the requirements of: | HYDRAULIC OIL AW 68 |
|--|---------------------|
| DIN 51524-2:2006-09                                | X                   |

### Properties and Specifications

| Property   | HYDRAULIC OIL AW 46 | HYDRAULIC OIL AW 68 |
|--|---------------------|---------------------|
| Grade  | ISO 46              | ISO 68              |
| Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130      | 1A                  | 1A                  |
| Density @ 15 C, kg/l, ASTM D1298                           | 0.876               | 0.882               |
| Emulsion, Time to 3 mL Emulsion, 54 C, min, ASTM D1401     | 15                  | 20                  |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 226                 | 234                 |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 6.6                 | 8.2                 |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 44                  | 63.3                |
| Pour Point, °C, ASTM D97                                   | -24                 | -18                 |

| Property                    | HYDRAULIC OIL AW 46 | HYDRAULIC OIL AW 68 |
|-----------------------------|---------------------|---------------------|
| Viscosity Index, ASTM D2270 | 98                  | 98                  |

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2021

Energy lives here™

**ExxonMobil**

Exxon Mobil ESso XTO ENERGY

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved