



Mobil SuperBox 15W-40

Mobil Commercial Vehicle Lube , Indonesia

High Performance Premium Engine Oil

Product Description

Mobil Superbox 15W-40 is a high performance engine oil that protects your engine performing frequent accelerations to enable a comfortable and safe drive in stop-and-go traffic.

Mobil Superbox 15W-40 is recommended by ExxonMobil for use in gasoline and diesel light duty vehicles.

Features and Benefits

Mobil SuperBox 15W-40 provides :

- High high temperature protection
- Strong engine wear protection

Maintains engine cleanliness

Applications

Recommended by ExxonMobil for use in:

- Stop and Go City Driving
- Gasoline and Diesel Engine

Heavy loading in light trucks and vans

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil SuperBox 15W-40 is recommended by ExxonMobil for use in applications requiring:
API SJ
API CF
ACEA E2

Typical Properties

Mobil SuperBox 15W-40	
SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	108
cSt @ 100°C	14.7

Mobil SuperBox 15W-40	
Viscosity Index, ASTM D 2270	140
Sulfated Ash, wt%, ASTM D 874	1.0
Total Base #, mg KOH/g, ASTM D 2896	9
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	227
Density @15 °C kg/l, ASTM D 4052	0.880

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil Asia Pacific Pte Ltd
 Jakarta Representative Office
 Wisma GKBI 27th Floor
 Jl. Jenderal Sudirman No. 28
 Jakarta 10210
 Indonesia

+62 21 574 0707

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved