



## Mobil SuperBox Advanced 10W-40

Mobil Commercial Vehicle Lube , Indonesia

Premium Synthetic Technology Engine Oil

### Product Description

Mobil Superbox Advanced 10W-40 is a premium engine oil formulated with synthetic technology, to provide superior engine performance for smooth acceleration and a comfortable drive in stop-and-go traffic.

Mobil Superbox Advanced 10W-40 is a premium engine oil formulated with synthetic technology, to provide superior engine performance for frequent accelerations to enable a comfortable and safe drive in stop-and-go traffic.

Mobil Superbox Advanced 10W-40 is recommended by ExxonMobil for use in gasoline and diesel light duty vehicles.

### Features and Benefits

Mobil SuperBox Advanced 10W-40 provides:

- Excellent high temperature protection
- Increased engine wear protection

Very Good engine cleanliness

### Applications

Recommended by ExxonMobil for use in:

- Stop and Go City Driving
- Gasoline and Diesel Engines (without Diesel Particulate Filter)
- Heavy loading in light trucks and vans

High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

<b>Mobil SuperBox Advanced 10W-40 meets or exceeds the requirements of:</b>	-
API SL	-

<b>Mobil SuperBox Advanced 10W-40 is recommended by ExxonMobil for use in applications requiring:</b>	-
API CF	-

### Typical Properties

<b>Mobil SuperBox Advanced 10W-40</b>	
SAE Grade	10W-40

<b>Mobil SuperBox Advanced 10W-40</b>	
Viscosity, ASTM D 445	
cSt @ 40°C	96
cSt @ 100°C	14.4
Viscosity Index, ASTM D 2270	155
Sulfated Ash, wt%, ASTM D 874	1.3
HTHS Viscosity, mPa·s @ 150°C, ASTM D4683	3.8
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	228
Density @ 15 °C, kg/l, ASTM D4052	0.870

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil Asia Pacific Pte Ltd  
 Jakarta Representative Office  
 Wisma GKBI 27th Floor  
 Jl. Jenderal Sudirman No. 28  
 Jakarta 10210  
 Indonesia

+62 21 574 0707

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved