



EZL 799 A

Mobil Passenger Vehicle Lube , Indonesia

Product Description

EZL 799 A is a high performance transmission fluid for automatic transmission (AT) and continuously variable transmission (CVT) applications.

Features and Benefits

Excellent flow properties at low start-up temperatures and high operating temperatures

Excellent shift performance and vehicle driveability

Excellent oxidation stability, less fluid breakdown in high-temperature service

Good viscosity stability

Good wear protection for maximum transmission life

Dependable protection against rust and corrosion

Applications

EZL 799 A is designed to meet the specific requirements of selected automated transmissions. It is used in both ATF and CVTF applications.

EZL 799 A is recommended by ExxonMobil for use in Punch VT2/VT3 transmissions, which are used in specific vehicle models made by several Chinese car manufacturers including Great Wall Motors, Changan Auto, Dong Feng and Geely. It is also specified for ZF applications requiring a ZF 481336 fluid (ZFST VT1F, CVT unit).

Properties and Specifications

Property	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.0
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	39
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	38,000
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130	1a
Foam, Sequence III, Tendency, ml, ASTM D892	10/0
Foam, Sequence IV, Tendency, ml, ASTM D6082	40/0
Flash Point, Cleveland Open Cup, °C, ASTM D92	184

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

ExxonMobil Asia Pacific Pte Ltd
Jakarta Representative Office
Wisma GKBI 27th Floor
Jl. Jenderal Sudirman No. 28
Jakarta 10210
Indonesia

+62 21 574 0707

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2021 Exxon Mobil Corporation. All Rights Reserved