



## Mobil Delvac Modern 15W-40 Extreme Defense V2

Mobil Commercial Vehicle Lube , India

Synthetic Technology Commercial Vehicle Engine Oil

### Product Description

Mobil Delvac Modern 15W-40 Extreme Defense V2 is an extra high performance diesel engine oil that provides excellent lubrication of today's diesel engines promoting extended engine life. This extra high performance has been recommended based on experience in wide variety of industries, applications, and fleets.

### Features and Benefits

Mobil Delvac Modern 15W-40 Extreme Defense V2 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralisation
Stay-in-grade shear stability	Wear protection and viscosity control
Advanced detergency/dispersancy	Cleaner engines and longer component life
Improved soot handling	Improved viscosity control and used oil pumpability
Excellent low temperature properties	Start-up wear protection
Component compatibility	Longer gasket and seal life

### Applications

- Naturally aspirated and turbo-charged diesel powered equipment.
- On-highway light and heavy-duty trucking.
- Off-highway industries including: construction, mining, quarrying and agriculture.

### Specifications and Approvals

This product meets or exceeds the requirements of:
API CI-4 PLUS

### Properties and Specifications

Property	
Grade	SAE 15W-40

Property	
Ash, Sulfated, mass%, ASTM D874	1.2
Density @ 15 C, g/cm <sup>3</sup> , ASTM D1298	0.877
Flash Point, Cleveland Open Cup, °C, ASTM D92	220
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.5
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	109
Total Base Number, mgKOH/g, ASTM D2896	8.5
Viscosity Index, ASTM D2270	137

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2021

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,  
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved