



Mobil Delvac TM Genuine CH-4 Oil 15W-40

Mobil Commercial Vehicle Lube , India

High Performance Diesel Engine Oil

Product Description

Mobil Delvac TM Genuine CH-4 Oil 15W-40 is a high performance diesel engine oil that provides proven protection of diesel engines operating in severe conditions for both On and Off-highway applications. Mobil Delvac TM Genuine CH-4 Oil 15W-40 is primarily intended for use in Tata Motors Diesel Commercial Vehicles. The technology in Mobil Delvac TM Genuine CH-4 Oil 15W-40 delivers excellent performance in both modern diesel engines as well as older models.

Features and Benefits

The technology in Mobil Delvac TM Genuine CH-4 Oil 15W-40 delivers excellent performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Component compatibility	Longer gasket and seal life

Applications

It is designed as per requirement of Engine oil for use in BS III/ BS IV Commercial vehicle diesel engines manufactured by Tata Motors. Approved by TATA Motors as per their specification TSS 6571 for API CH-4 Engine Oil.

Specifications and Approvals

Mobil Delvac TM Genuine CH-4 Oil 15W-40 meets or exceeds the requirements of the following industry specifications	
API CH-4	X

Mobil Delvac TM Genuine CH-4 Oil 15W-40 has the following OEM approvals:	
TATA Motors TSS 6571	X

Typical Properties

Mobil Delvac TM Genuine CH-4 Oil 15W-40	
SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	103.7

Mobil Delvac TM Genuine CH-4 Oil 15W-40	
cSt @ 100°C	14.4
Viscosity Index, ASTM D 2270	142
Sulfated Ash, wt%, ASTM D 874	1.3
Total Base #, mg KOH/g, ASTM D 2896	10
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	234
Density @15.6 °C kg/l, ASTM D 4052	0.86

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,

Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved