



## Mobil Delvac TM Genuine CI-4 PLUS Oil 15W-40

Mobil Commercial Vehicle Lube , India

Extra High Performance Diesel Engine Oil

### Product Description

Mobil Delvac TM Genuine CI-4 PLUS Oil 15W-40 is an extra high performance diesel engine oil that provides excellent lubrication of today's diesel engines promoting extended engine life. This extra high performance has been proven in the field in a wide variety of industries, applications, and mixed fleets. It is recommended by ExxonMobil for use in Tata Motors Commercial Vehicles with requirement of engine oil meeting TSS 6576.

### Features and Benefits

Mobil Delvac TM Genuine CI-4 PLUS Oil 15W-40 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralisation
Stay-in-grade shear stability	Wear protection and viscosity control
Advanced detergency/dispersancy	Cleaner engines and longer component life
Improved soot handling	Improved viscosity control and used oil pumpability
Excellent low temperature properties	Start-up wear protection
Component compatibility	Longer gasket and seal life

### Applications

It is designed as per requirement of Engine oil for use in BS III/ BS IV Commercial vehicle diesel engines manufactured by Tata Motors. Approved by TATA Motors as per their specification TSS 6576 for API CI-4 PLUS Engine Oil

### Specifications and Approvals

Mobil Delvac TM Genuine CI-4 PLUS Oil 15W-40 is recommended by ExxonMobil for use in applications requiring	X
API CI-4 PLUS	

Mobil Delvac TM Genuine CI-4 PLUS Oil 15W-40 has the following OEM approvals:	
TATA Motors TSS 6576	X

### Typical Properties

Mobil Delvac TM Genuine CI-4 PLUS Oil 15W-40	
SAE Grade	15W-40

Mobil Delvac TM Genuine CI-4 PLUS Oil 15W-40	
Viscosity, ASTM D 445	
cSt @ 40°C	109
cSt @ 100°C	14.5
Viscosity Index, ASTM D 2270	137
Sulfated Ash, wt%, ASTM D 874	1.35
Total Base # , mg KOH/g, ASTM D 2896	11
Pour Point, °C, ASTM D 97	-39
Flash Point, °C, ASTM D 92	226
Density @ 15°C kg/l, ASTM D 4052	0.88

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,  
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved