



## Mobil Delvac™ TM Genuine Long Drain Axle Oil 80W 140

Mobil Commercial Vehicle Lube , India

Heavy Duty Automotive Gear Lubricants

### Product Description

Mobil Delvac™ TM Genuine Long Drain Axle Oil 80W-140 is designed specifically for use in Rear Axles and Live Front Axles designed by Tata Motors Ltd. The oil is formulated for improved durability and provide extended drain period.

### Applications

Recommended by ExxonMobil for use in:

- Rear Axles and Live Front Axles designed by Tata Motors Ltd

### Specifications and Approvals

This product has the following builder approvals:

Tata Supply Specification : TSS 6578

### Properties and Specifications

| Property   |             |
|--|-------------|
| Grade  | SAE 80W-140 |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 27.0        |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 277         |
| Viscosity Index, ASTM D2270                                | 128         |
| Pour Point, °C, ASTM D97                                   | -24         |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 198         |
| Density @ 15.6 C, g/ml, ASTM D4052                         | 0.888       |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

The Mobil logotype, the Pegasus design, and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,

Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon Mobil Esso XTO  
ENERGY

© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved