



Mobilube™ 1 SHC 75W-90

Mobil Commercial Vehicle Lube , India

Fully Synthetic Automotive Gear Lubricant

Product Description

Mobilube 1 SHC 75W-90 is a fully synthetic, high performance commercial gear lubricant formulated using advanced base oils and the latest technology additive system. This lubricant is engineered for heavy duty manual transmissions and rear axles where operations require gear lubricants with excellent load-carrying capability over wide operating temperatures and where extreme pressures and shock loading are expected. Mobilube 1 SHC 75W-90 has excellent thermal and oxidation stability, high inherent Viscosity Index (VI), extremely low pour point, and outstanding low temperature fluidity.

The state-of-the-art technology behind Mobilube 1 SHC 75W-90 delivers outstanding viscosity-temperature properties necessary for wide temperature range applications, optimised protection against thermal degradation and oxidation, wear and corrosion, shear stability, extended service capability, and potential fuel economy improvement. Mobilube 1 SHC 75W-90 incorporates the latest technology in synthetic basestocks and advanced additives providing significant advantages over conventional gear oils. This technology also ensures effective lubrication since this product remains fluid without channeling at subzero temperatures. Mobilube 1 SHC 75W-90 meets or exceeds the requirements of the API Service MT-1/GL-4/GL-5 gear oil service classifications.

Features and Benefits

Today's technology has vastly improved the performance capabilities of heavy duty on and off highway equipment load, torque, speed, and control through innovative drivetrain designs. These designs have changed and increased the requirements of lubricants to deliver higher levels of performance, increased productivity, and reduced operating costs. For heavy-duty final drives, friction control, wear protection, thermal stability, shear stability, rust and corrosion prevention, and seal protection are features that must be optimally balanced to provide extended gear and seal life, smooth operation, improved fuel economy, and high load high torque capability over a wide range of applications. Mobilube 1 SHC 75W-90 is engineered to deliver exceptional performance and reduce total lube-related operating cost in modern heavy duty drivetrains. The key benefits include:

Features	Advantages and Potential Benefits
Exceptional thermal stability and resistance to high temperature oxidation	Long gear and bearing life due to minimal deposits Long seal life
Outstanding protection against low speed/high torque wear, spalling, and against high speed scoring	Increased load-carrying capability. Reduced maintenance costs and long equipment life
Excellent shear stability	Retains viscosity and film strength under severe operating conditions to prevent wear
Excellent rust, staining, and corrosion protection of copper and its alloys	Improved synchroniser performance and long component life
Enhanced frictional properties	Fuel economy potential and improved shiftability
Outstanding low temperature fluidity versus mineral oils	Reduced wear and ease of start up--even in arctic conditions
Wide multipurpose capability	One lubricant for heavy-duty manual transmissions and rear axles
Good resistance to foaming	Maintains film strength for effective lubrication
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination

Applications

Recommended by ExxonMobil for use in:

- On-highway light- and heavy-duty trucks, busses, vans, and cars
- Off-highway industries including: construction, quarrying, and agriculture
- Transmissions and axles and other applications where lubricants meeting API GL-4, GL-5 or MT-1 where mild extreme pressure gear lubricants are recommended
- Not intended for automatic, manual, or semi-automatic transmissions for which engine oil or automatic transmission fluids are recommended

- Applications where extended service intervals and warranties are required

Specifications and Approvals

Mobilube 1 SHC 75W-90 meets or exceeds the requirements of the following industry and builder specifications:	
ZF TE-ML 07A	X
Scania STO 1.0	X
ZF TE-ML 08	X
BOSCH TE-ML 08	X

Mobilube 1 SHC 75W-90 has the following builder approvals:	
JSC AVTODIZEL YaMZ Gearboxes	X
MAN 341 Typ Z2	X
MAN 342 Typ S1	X
MB-Approval 235.8	X
ZF TE-ML 02B/05B/12L/12N/16F/17B/19C/21A	X
SAE J2360	X

This product is recommended by ExxonMobil for use in applications requiring:	
API GL-4	X
MAN 341 Typ E3	X

This product meets or exceeds the requirements of:	
API GL-5	X
API MT-1	X

Typical Properties

Mobilube 1 SHC 75W-90	
SAE Grade	75W-90
Viscosity, ASTM D 445	
cSt @ 40°C	102
cSt @ 100°C	15.1
Viscosity Index, ASTM D 2270	156
Pour Point, °C, ASTM D 97	-54
Flash Point, °C, ASTM D 92	202
Density @ 15°C kg/l, ASTM D 4052	0.87

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2019

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,

Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved