



MOBIL DELVAC™ EXTRA LONG LIFE GREASE

Mobil Grease , India

High performance automotive grease

Product Description

Mobil Delvac™ extra long life grease exhibits excellent resistance to softening under severe working and provides good adhesion and cohesion. An extreme-pressure additive provides exceptional protection against wear and shock loads, while additional additives enhance resistance to high-temperature oxidation and protection against rust. Mobil Delvac extra long life grease is recommended for use in heavy-duty trucks, especially wheel bearings, hinge and bucket pins, U-joints, and fifth wheels. It is also recommended for construction and mining sector applications, particularly for the lubrication of plain and antifriction bearings in contractor and mining vehicles working under severe operating and weather conditions.

Features and Benefits

Mobil Delvac™ extra long life grease is high performance product designed by our formulation technologists and backed by our world-wide technical support staff. A key factor in the excellent adhesion and cohesion properties and high drop point of Mobil Delvac extra long life grease is the proprietary manufacturing technology developed at our research facilities and adopted by our modern manufacturing facilities. This product uses specially selected additives to provide excellent oxidation stability, rust and corrosion control, resistance to water contamination as well as anti-wear and EP protection. Mobil Delvac extra long life grease offers the following features and potential benefits:

| Features | Advantages and Potential Benefits |
|---|--|
| Superb resistance to water washout and spray-off | Helps assure proper lubrication and protection even in the most severe water exposure conditions |
| Highly adhesive and cohesive structure | Excellent grease tenacity, helps reduce leakage and extend re-lubrication intervals for reduced maintenance requirements |
| Excellent rust and corrosion resistance P | Protection of lubricated parts even in hostile aqueous environments |
| Very good resistance to thermal, oxidative and structural degradation at high temperature | Helps extend grease life and enhance bearing protection in high temperature applications helping to reduce maintenance and replacement costs |
| Very good anti-wear and EP performance | Reliable protection of lubricated equipment, even under conditions of high sliding with potential for extended equipment life and reduced unanticipated downtime |
| Broad multi-purpose application | Provides potential for inventory rationalization and reduced inventory costs |

Applications

Mobil Delvac™ extra long life grease is used in a wide range of equipment for on-highway and off-highway in the fleet, mining, farming and construction sectors. Mobil Delvac extra long life grease is recommended for use in heavy-duty trucks, especially wheel bearings, hinge and bucket pins, U-joints, fifth wheel and chassis components. Its sticky formulation stays in applications longer.

Specifications and Approvals

| |
|--|
| MOBIL DELVAC EXTRA LONG LIFE GREASE meets or exceeds the requirements of: |
| DIN 51825:2004-06 - KP 2 N -20 |

Properties and Specifications

| Property | |
|--|-----------------|
| Grade | NLGI 2 |
| Thickener Type | Lithium Complex |
| Base Oil Viscosity of Greases @ 40 C, mm ² /s, AMS 1697 | 220 |
| Color, Visual | Dark blue |
| Penetration, 60X, 0.1 mm, ASTM D217 | 280 |
| Dropping Point, °C, ASTM D2265 | 280 |
| Timken OK Load, kg, ASTM D2509 | 18 |
| Corrosion Preventive Properties, Rating, ASTM D1743 | Pass |
| Roll Stability, Penetration Consistency Change, 0.1 mm, ASTM D1831 | 0 |
| Oxidation Stability, Pressure Drop, 100 h, kPa, ASTM D942 | 35 |
| Four-Ball Extreme Pressure Test, Weld Point, kgf, ASTM D2596 | 315 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2021

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All

Rights Reserved