

## Mobil Super™ 4T 20W-40

Mobil Passenger Vehicle Lube, India

High Performance Four-Stroke Motorcycle Engine Oil

## **Product Description**

Mobil Super $^{\text{TM}}$  4T 20W-40 is a high performance conventional four-stroke motorcycle engine oil primarily intended for general use in all types of four-stroke motor and engines.

#### Features and Benefits

Mobil Super 4T 20W-40 combine highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protectic corrosion protection. Key features and benefits include:

| Features                        | Advantages and Potential Benefits               |
|---------------------------------|---|
| Good wear protection            | Helps extend engine life                        |
| Thermal and oxidation stability | Helps keep engines clean for smoother operation |
| Good corrosion protection       | Protects critical engine components             |
| Broad viscosity range           | Year round engine protection and performance    |

## Specifications and Approvals

| This product meets or exceeds the requirements of: |  |
|--|--|
| API SL   |  |

#### Properties and Specifications

| Property                                      |            |
|---|------------|
| Grade   | SAE 20W-40 |
| Ash, Sulfated, mass%, ASTM D874               | 0.8        |
| Density @ 15.6 C, g/ml, ASTM D4052            | 0.88       |
| Flash Point, °C, ASTM D92                     | 230        |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 15         |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445  | 122        |
| Pour Point, °C, ASTM D97                      | -30        |

# Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building, Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All promay not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intenoverride or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

