



Mobil Super™ 3000 0W-20

Mobil Passenger Vehicle Lube , India

Full Synthetic Engine Oil

Product Description

Mobil Super™ 3000 0W-20 All-In-One Protection is brought to you by the makers of Mobil 1. This full synthetic engine oil is tailored for smoother acceleration provides outstanding engine wear protection even under the most demanding driving conditions.

Mobil Super™ 3000 0W-20 All-In-One Protection is formulated with Heat-Activated Anti-Wear Molecules technology which provides superior engine protection at high temperature and proven in latest API SP engine test to provide better engine wear protection up to 65%\*.

Mobil Super™ 3000 0W-20 All-In-One Protection is proven during API SP engine test to reduce the damaging Low Speed Pre-Ignition problem in modern engines and helps to improve engine efficiencies and prolong engine life.

Features and Benefits

Features and Benefits

- Suitable for Toyota, Honda, Nissan, Hybrid and other newer Japanese ECO gasoline engines
- Improved fuel economy by up to 2% \*\*
- Heat-activated anti-wear molecule provides high temperature wear protection while keeping your engine clean
- Provides better engine wear protection up to 65%\*

\* Based on Sequence IWB (Iron Wear) test result versus API SP engine test requirement. Result varies subject to engine, temperature and actual driving conditions.

\*\* Based on Sequence VIE test result versus API SP industry reference oil. Result varies subject to engine, temperature and actual driving conditions.

Applications

Mobil Super™ 3000 0W-20 All-In-One Protection is recommended for gasoline fueled automobiles, especially for Hybrid and ECO cars where SAE 0W-20 viscosity grade is recommended. It meets or exceeds the requirements of latest API SP, SN PLUS, SN, SM, SL and ILSAC GF-6A. It also meets Ford WSS-M2C947-A, Ford WSS-M2C947-B1, Ford WSS-M2C962-A1 engine oil specifications.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SJ
API SL
API SM
API SN
API SN PLUS
API SN PLUS RESOURCE CONSERVING
API SN Resource Conserving
Ford WSS-M2C947-B1

This product meets or exceeds the requirements of:
ILSAC GF-6A
API SP

Properties and Specifications

Property	
Grade	SAE 0W-20
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	8.5
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	45
Viscosity Index, ASTM D2270	170
Density @ 15.6 C, g/ml, ASTM D4052	0.847
Pour Point, °C, ASTM D97	-42
Flash Point, Cleveland Open Cup, °C, ASTM D92	220
Ash, Sulfated, mass%, ASTM D874	0.8
Total Base Number, mgKOH/g, ASTM D2896	7.5
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	24700
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.6

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024  
ExxonMobil Services & Technology Private Limited  
(CIN: U74900KA2015FTC080245)  
Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,  
Whitefield Main Road, Bangalore – 560048, Karnataka, India  
  
+918071085300  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

ExxonMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All rights reserved.

