



## Mobil Special™ 20W-50

Mobil Passenger Vehicle Lube , India

High Performance Motor Oil

### Product Description

Mobil Special™ 20W-50 is a high performance motor oil for all types of vehicles. Mobil Special 20W-50 delivers engine protection and cleanliness. Mobil Special 20W-50 is recommended for use in a wide range of applications and operating conditions.

### Features and Benefits

- Helps reduce engine wear and corrosion
- Helps keep engine clean
- Multigrade motor oil allowing easier starts at low temperatures
- Good high temperature properties.

### Applications

Best for all types of vehicles requiring API SN recommended by OEMs.

### Specifications and Approvals

**This product meets or exceeds the requirements of:**

API SL

API SM

API SN

### Properties and Specifications

Property	
Grade	SAE 20W-50
Viscosity Index, ASTM D2270	122
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	18
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 <sup>(6)</sup> sec <sup>(-1)</sup> , mPa.s, ASTM D4683	4.8
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	163
Flash Point, Cleveland Open Cup, °C, ASTM D92	240
Ash, Sulfated, mass%, ASTM D874	0.9

Property	
Total Base Number, mgKOH/g, ASTM D2896	7.4
Mini-Rotary Viscometer, Apparent Viscosity, -20 C, mPa.s, ASTM D4684	17400
Density @ 15 C, g/ml, ASTM D4052	0.883
Pour Point, °C, ASTM D97	-30

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2022

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,  
Whitefield Main Road, Bangalore – 560048, Karnataka, India


+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved