



Mobil Super™ Everyday Protection 20W-50

Mobil Passenger Vehicle Lube , India

Everyday Protection Premium Mineral Engine Oil

Product Description

Mobil Super™ 1000 20W-50 Everyday Protection is brought to you by the makers of Mobil 1. This premium mineral engine oil is designed for extended engine life and meet your most demanding vehicle maintenance needs.

Mobil Super™ 1000 20W-50 Everyday Protection with ExEngine Molecule technology is engineered with age defying and anti-wear ingredient to protect against life shortening engine wear. It was proven in latest API SP engine test to provides better engine wear protection up to 65%*.

Mobil Super™ 1000 20W-50 Everyday Protection is proven during API SP engines test in reduces damaging Low Speed Pre-Ignition (LSPI) problem common in modern engines. This helps to improve engine efficiencies and prolong engine life.

Features and Benefits

- Suitable for most Japanese and Korean gasoline engines
- ExEngine Molecule is engineered with age defying and anti-wear ingredient to protect against life shortening engine wear
- Proprietary Extengine Molecules technology
- Better engine wear protection up to 65%*
- Improve engine efficiencies by reducing Engine Low Speed Pre-Ignition (LSPI)
- Extended protection against deposits formation
- Engine protection during start up
- Helps combat sludge

* Based on Sequence IWB (Iron Wear) test result versus API SP engine test requirement. Result varies subject to engine, temperature and actual driving conditions.

Applications

Mobil Super™ 1000 20W-50 Everyday Protection exceeds latest API SP gasoline engine oil test specification. It can be used in gasoline engines that requires API SP/SN PLUS/SN/SM specifications

Mobil Super™ 1000 20W-50 Everyday Protection have been formulated to be suitable for use in nearly all vehicles. ExxonMobil particularly recommend Mobil Super 1000 Everyday Protection for daily driving under normal conditions:

- Nearly all gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:

API SL

API SM

API SN

API SN PLUS

API SP

Properties and Specifications

Property	
Grade	SAE 20W-50
Pour Point, °C, ASTM D97	-27
Flash Point, Cleveland Open Cup, °C, ASTM D92	239
Ash, Sulfated, mass%, ASTM D874	0.8
Viscosity Index, ASTM D2270	128
Total Base Number, mgKOH/g, ASTM D2896	7.5
Density @ 15.6 C, g/ml, ASTM D4052	0.882
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	17
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	147
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.5
Mini-Rotary Viscometer, Apparent Viscosity, -20 C, mPa.s, ASTM D4684	14900

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2023

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,

Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved