



## Mobil Super™ All-in-One Protection SUV Pro 5W-30

Mobil Passenger Vehicle Lube , India

Full synthetic engine oil delivering All-in-One Protection for every terrain

### Product Description

Mobil Super™ SUV Pro is formulated to deliver All-in-One Protection for every terrain. From daily commutes in city traffic to weekend drives over rugged terrain, Mobil Super™ SUV Pro is feature-packed for effortless protection.

### Features and Benefits

- Full synthetic engine oil delivering protection for every terrain
- 79% better engine wear protection<sup>^</sup>
- All-weather protection for longer engine life
- Heat-activated anti-wear protection
- Low speed pre-ignition protection
- Suitable for petrol and diesel SUVs

<sup>^</sup> Based on ASTM D6891 (Seq. IVA) test results versus API SN engine test requirement

### Applications

Mobil Super™ All-in-One Protection SUV Pro 5W-30 is suitable for use in petrol and diesel SUVs.

Always consult your owner's manual to check the recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

This product meets or exceeds the requirements of:
API SM
API SN
API SN PLUS
ACEA A3/B4-16

This product is recommended for use in applications requiring:
API CF
API CF-4
API CG-4

## Properties and Specifications

Property	
Grade	SAE 5W-30
Density @ 15 C, g/ml, ASTM D1298	0.857
Ash, Sulfated, mass%, ASTM D874	1.16
Flash Point, Cleveland Open Cup, °C, ASTM D92	240
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.5
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	12.3
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	74
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	29800
Viscosity Index, ASTM D2270	165
Total Base Number, mgKOH/g, ASTM D2896	11
Pour Point, °C, ASTM D97	-39

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,

Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All

Rights Reserved