



Mobil Super HP 10W-30

Mobil Passenger Vehicle Lube , India

Extra High Performance Motor Oil

Product Description

Mobil Super HP 10W-30 is a high-quality multi-grade motor oil whose performance meets the industry standards of modern gasoline vehicle engines.

Features and Benefits

Mobil Super HP 10W-30 can keep the engine clean and running smoothly. It also protects the engine with high-quality mineral oil and additive formulations.

Mobil Super HP 10W-30 maintains the overall cleanliness of the engine, help prevent harmful carbon deposits and sludge accumulation formed in high-temperature areas of the engine. It also help prevent wear and corrosion, thereby reducing maintenance costs.

Recommended for highway or frequent stop-start driving conditions.

Features	Advantages and Potential Benefits
Good thermal and oxidative stability	Reduce engine carbon deposits and reduce harmful sludge and carbon deposits formed in high-temperature areas inside the engine
Anti-friction and anti-wear system	Reduce wear and tear, thereby reducing maintenance costs
High viscosity index, high mechanical shear stability	Improve lubrication at room temperature and high temperature. Good high and low temperature protection performance under severe driving conditions

Applications

Best for all types of vehicles requiring API SL recommended by OEMs.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SL

Properties and Specifications

Property	
Grade	SAE 10W-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	243
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	69

Property	
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.2
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Viscosity Index, ASTM D2270	136
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	15200
Pour Point, °C, ASTM D97	-36
Density @ 15 C, g/ml, ASTM D4052	0.869
Ash, Sulfated, mass%, ASTM D874	0.9
Total Base Number, mgKOH/g, ASTM D2896	7.6

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2021

ExxonMobil Services & Technology Private Limited
(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,
Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved